

STATE WATER CONTROL BOARD
Amend and Reissue Existing Nonmetallic Mineral Mining General Permit

9VAC25-190-10. Definitions.

The words and terms used in this chapter shall have the meanings defined in the State Water Control Law Chapter 3.1 (§ 62.1-44.2 et seq.) of Title 62.1 of the Code of Virginia and the Virginia Pollutant Discharge Elimination System (VPDES) Permit Regulation (9VAC25-31) unless the context clearly indicates otherwise. Additionally, for the purposes of this chapter:

"Best management practices" or "BMPs" means schedules of activities, practices (and prohibitions of practices), structures, vegetation, maintenance procedures, and other management practices to prevent or reduce the discharge of pollutants to surface waters. BMPs also include treatment requirements, operating procedures, and practices to control plant site run-off, spillage or leaks, sludge or waste disposal, or drainage from raw material storage.

"Colocated facility" means an industrial activity other than mineral mining operating on a site where the primary industrial activity is mineral mining. Such an activity must have wastewater characteristics similar to those of the mineral mine and be located within the permitted mining area. The term refers to activities that are commonly found at mining sites such as manufacturing of ready-mix concrete (SIC Code 3273), concrete products (SIC Codes 3271 and 3272), and asphalt paving materials (SIC Code 2951) except asphalt emulsion manufacturing. It does not mean industrial activity that is specifically excluded from this permit.

"Department" or "DEQ" means the Virginia Department of Environmental Quality.

"Industrial activity" means activity associated with mineral mining facilities generally identified by SIC Major Group 14 including active or inactive mining operations that discharge stormwater that has come into contact with any overburden, raw material, intermediate products, finished products, by-products or waste products located on the site of such operations. (Inactive mining operations are mining sites that are not being actively mined, but which have an identifiable owner/operator; inactive mining sites do not include sites where mining claims are being maintained prior to disturbances associated with the extraction, beneficiation, or processing of mined materials, nor sites where minimal activities are undertaken for the sole purpose of maintaining a mining claim.) Industrial activity also includes facilities classified under other SIC codes that may be colocated within the mineral mine permit area, unless they are expressly excluded by this general permit.

"Municipal separate storm sewer system" or "MS4" means a conveyance or system of conveyances, including roads with drainage systems, municipal streets, catch basins, curbs, gutters, ditches, man-made channels, or storm drains (i) owned or operated by a state, city, town, county, district, association, or other public body (created by or pursuant to state law) having jurisdiction over disposal of sewage, industrial wastes, stormwater, or other wastes, including special districts under state law such as a sewer district, flood control district or drainage district, or similar entity, or an Indian tribe or an authorized Indian tribal organization, or a designated and approved management agency under § 208 of the Clean Water Act that discharges to surface waters of the state; (ii) designed or used for collecting or conveying stormwater; (iii) that is not a combined sewer; and (iv) that is not part of a publicly owned treatment works (POTW).

"Permittee" means the owner of a nonmetallic mineral mine covered under this general permit.

"Process wastewater" means any wastewater used in the slurry transport of mined material, air emissions control, or processing exclusive of mining, and any other water that becomes

commingled with such wastewater in a pit, pond, lagoon, mine, or other facility used for treatment of such wastewater. It includes mine pit dewatering, water used in the process of washing stone, noncontact cooling water, wastewater from vehicle or equipment degreasing activities, vehicle washing and return water from operations where mined material is dredged and miscellaneous plant cleanup wastewaters.

"Run-off coefficient" means the fraction of total rainfall that will appear at the conveyance as run-off.

"SIC" means the Standard Industrial Classification Code or Industrial Grouping from the U.S. Office of Management and Budget Standard Industrial Classification Manual, 1987 Edition.

"Significant materials" includes, but is not limited to, raw materials; fuels; materials such as solvents, detergents, and plastic pellets; finished materials; hazardous substances designated under Section 101(14) of the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) (42 USC § 9601 et seq.); any chemical the owner is required to report pursuant to Section 313 of the Emergency Planning and Community Right-to-Know Act (EPCRA) (42 USC § 11001 et seq.); fertilizers; pesticides; and waste products such as ashes, slag and sludge (including pond sediments) that have the potential to be released with stormwater discharges.

"Significant spills" includes, but is not limited to, releases of oil or hazardous substances in excess of reportable quantities under § 311 of the Clean Water Act (see 40 CFR 110.10 and 40 CFR 117.21) or § 102 of the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) (42 USC § 9601 et seq.) (see 40 CFR 302.4).

"Stormwater" means stormwater run-off, snow melt run-off, and surface run-off and drainage.

"Stormwater discharge associated with industrial activity" means the discharge from any conveyance that is used for collecting and conveying stormwater and that is directly related to manufacturing, processing or raw materials storage areas at an industrial plant. The term does not include discharges from facilities or activities excluded from the VPDES program under 9VAC25-31. For the categories of industries identified in the "industrial activity" definition, the term includes, but is not limited to, stormwater discharges from industrial plant yards; immediate access roads and rail lines used or traveled by carriers of raw materials, manufactured products, waste material, or by-products used or created by the mineral mine; material handling sites; refuse sites; sites used for the application or disposal of process wastewaters; sites used for the storage and maintenance of material handling equipment; sites used for residual treatment, storage, or disposal; shipping and receiving areas; manufacturing buildings; storage areas (including tank farms) for raw materials, and intermediate and finished products; and areas where industrial activity has taken place in the past and significant materials remain and are exposed to stormwater. For the purposes of this paragraph, material handling activities include the storage, loading and unloading, transportation, or conveyance of any raw material, intermediate product, finished product, by-product or waste product. The term excludes areas located on plant lands separate from the plant's industrial activities, such as office buildings and accompanying parking lots as long as the drainage from the excluded areas is not mixed with stormwater drained from the above described areas.

"Total maximum daily load" or "TMDL" means a calculation of the maximum amount of a pollutant that a waterbody can receive and still meet water quality standards and an allocation of that amount to the pollutant's sources. A TMDL includes wasteload allocations (WLAs) for point source discharges, and load allocations (LAs) for nonpoint sources or natural background or both, and must include a margin of safety (MOS) and account for seasonal variations.

"Twenty-five-year, 24-hour storm event" means the maximum 24-hour precipitation event with a probable recurrence interval of once in 25 years as established by the National Weather Service or appropriate regional or state rainfall probability information.

"Vehicle or equipment degreasing" means the washing or steam cleaning of engines of a vehicle or piece of equipment and other drive components in which the purpose is to clean and degrease and clean petroleum products from the equipment for maintenance. Washing the vehicle exterior for the purpose of removing sediment is not considered vehicle or equipment degreasing.

9VAC25-190-15. Applicability of incorporated references based on the dates that they became effective.

Except as noted, when a regulation of the U.S. Environmental Protection Agency set forth in Title 40 of the Code of Federal Regulations is referenced or adopted herein and incorporated by reference that regulation shall be as it exists and has been published as of July 1, 2013.

9VAC25-190-20. Purpose; delegation of authority; effective date of permit.

A. The purpose of this chapter is to establish General Permit Number VAG84 to regulate wastewater discharge from nonmetallic mineral mines as follows:

1. For active and inactive nonmetallic mineral mining facilities in SIC Major Group 14, this general permit covers discharges composed entirely of stormwater associated with industrial activity.
2. This general permit authorizes the discharge of process wastewater as well as stormwater associated with industrial activity from active and inactive mineral mines classified under SIC Codes 1411, 1422, 1423, 1429, 1442, 1455, 1459 excluding bentonite and magnesite mines, 1475, and 1499 excluding gypsum, graphite, asbestos, diatomite, jade, novaculite, wollastonite, tripoli or asphaltic mineral mines.
3. Coal mining, metal mining, and oil and gas extraction are not covered by this general permit.

B. The director, or an authorized representative, may perform any act of the board provided under this chapter, except as limited by § 62.1-44.14 of the Code of Virginia.

C. This general permit will become effective on July 1, 2014, and will expire June 30, 2019. For any covered owner, this general permit is effective upon compliance with all the provisions of 9VAC25-190-50 and the receipt of this general permit.

9VAC25-190-50. Authorization to discharge.

A. Any owner governed by this general permit is authorized to discharge process wastewater and stormwater as described in 9VAC25-190-20 A 1 and 2 to surface waters of the Commonwealth of Virginia provided that:

1. The owner submits a registration statement in accordance with 9VAC25-190-60, and that registration statement is accepted by the board;
2. The owner submits the required permit fee;
3. The owner complies with the applicable effluent limitations and other requirements of 9VAC25-190-70;
4. The owner has a mineral mining permit for the operation to be covered by this general permit that has been approved by the Virginia Department of Mines, Minerals and Energy, Division of Mineral Mining (or an associated waived program, locality, or state agency) under provisions and requirements of Title 45.1 of the Code of Virginia. Mineral mines located in bordering states with discharges in Virginia shall provide documentation that they have a mining permit from the appropriate state authority. Mineral mines owned

and operated by governmental bodies not subject to the provisions and requirements of Title 45.1 of the Code of Virginia are exempt from this requirement; and

5. The board has not notified the owner that the discharge is not eligible for coverage in accordance with subsection B of this section.

B. The board will notify an owner that the discharge is not eligible for coverage under this general permit in the event of any of the following:

1. The owner is required to obtain an individual permit in accordance with 9VAC25-31-170 B 3 of the VPDES Permit Regulation;

2. The owner is proposing to discharge to state waters specifically named in other board regulations that prohibit such discharges;

3. The discharge violates or would violate the antidegradation policy in the water quality standards at 9VAC25-260-30; or

4. The discharge is not consistent with the assumptions and requirements of an approved TMDL.

C. Compliance with this general permit constitutes compliance with the federal Clean Water Act and the State Water Control Law, with the exceptions stated in 9VAC25-31-60 of the VPDES Permit Regulation. Approval for coverage under this general permit does not relieve any owner of the responsibility to comply with any other applicable federal, state, or local statute, ordinance, or regulation.

D. Continuation of permit coverage.

1. Any owner that was authorized to discharge under the nonmetallic mineral mining general permit issued in 2009 and that submits a complete registration statement before July 1, 2014, is authorized to continue to discharge under the terms of the 2009 general permit until such time as the board either:

a. Issues coverage to the owner under this general permit; or

b. Notifies the owner that the discharge is not eligible for coverage under this general permit.

2. When the owner that was covered under the expiring or expired general permit has violated or is violating the conditions of that permit, the board may choose to do any or all of the following:

a. Initiate enforcement action based upon coverage under the 2009 general permit that has been continued;

b. Issue a notice of intent to deny coverage under the reissued general permit. If the general permit coverage is denied, the owner would then be required to cease the discharges authorized by coverage under the 2009 continued general permit or be subject to enforcement action for discharging without a permit;

c. Issue an individual permit with appropriate conditions; or

d. Take other actions authorized by the VPDES Permit Regulation (9VAC25-31).

9VAC25-190-60. Registration statement.

A. The owner seeking coverage under this general permit shall submit a complete VPDES general permit registration statement in accordance with this section, which shall serve as a notice of intent for coverage under the general VPDES permit for nonmetallic mineral mining facilities.

1. New facilities. Any owner proposing a discharge shall submit a complete registration statement at least 45 days prior to the date planned for commencement of the discharge.

2. Existing facilities.

a. Any owner covered by an individual VPDES permit that is proposing to be covered by this general permit shall submit a complete registration statement at least 210 days prior to the expiration date of the individual VPDES permit.

b. Any owner that was authorized to discharge under the VPDES general permit for nonmetallic mineral mining that became effective on July 1, 2009, and that intends to continue coverage under this general permit shall submit a complete registration statement to the board on or before April 1, 2014.

B. Late registration statements. Registration statements for existing facilities covered under subdivision A 2 b of this section will be accepted after June 30, 2014, but authorization to discharge will not be retroactive. Owners described in subdivision A 2 b of this section that submit registration statements after April 1, 2014, are authorized to discharge under the provisions of 9VAC25-190-50 D if a complete registration statement is submitted before July 1, 2014.

C. The required registration statement shall contain the following information:

1. Facility owner and operator or other contact name, address, email address, and telephone number;
2. Facility name, county, location, latitude, and longitude;
3. Description of mining activity;
4. Primary and secondary SIC codes;
5. Discharge information including:
 - a. A list of outfalls identified by outfall numbers;
 - b. Characterization of the type of each listed outfall's discharge as either process wastewater, stormwater, or process wastewater commingled with stormwater;
 - c. Characterization of the source of each listed outfall's discharge as either mine pit dewatering, stormwater associated with industrial activity (see definition in 9VAC25-190-10), stormwater not associated with industrial activity, ground water infiltration, wastewater from vehicle or equipment degreasing activities, vehicle washing and return water from operations where mined material is dredged, mined material washing, noncontact cooling water, miscellaneous plant cleanup wastewater, colocated facility discharges (identify the colocated facility), other discharges not listed here (describe), or any combination of the above;
 - d. The receiving stream, including wetlands for each outfall listed;
 - e. The latitude and longitude for each outfall listed; and
 - f. Indicate which stormwater outfalls will be representative outfalls that require a single discharge monitoring report (DMR). For stormwater outfalls that are to be represented by other outfall discharges, provide a description of the activities associated with those outfalls and explain why they are substantially the same as the representative outfall to be sampled;
6. Indicate if the facility has a current VPDES permit and the permit number if it does;
7. Description of wastewater treatment or reuse/recycle systems or both;
8. List of any chemicals added to water that could be discharged;
9. List of colocated facilities;
10. Indicate if the facility is a hazardous waste treatment, storage or disposal facility;

11. Schematic drawing showing water flow from source to water-using industrial operations to waste treatment and disposal, and disposal of any solids removed from wastewater;

12. Aerial photo or scale map that clearly shows the property boundaries, plant site, drainage areas associated with each outfall, locations of all mine pit dewatering, existing, significant sources of materials exposed to precipitation, stormwater or process wastewater outfalls and the receiving streams;

13. Evidence that the operation to be covered by this general permit has a mining permit that has been approved by the Virginia Department of Mines, Minerals and Energy, Division of Mineral Mining (or associated waived program) under the provisions and requirements of Title 45.1 of the Code of Virginia (or appropriate bordering state authorization). Mineral mines owned and operated by governmental bodies not subject to the provisions and requirements of Title 45.1 of the Code of Virginia are exempt from this requirement;

14. Mining permit number;

15. Whether the permitted outfall will discharge to a municipal separate storm sewer system (MS4). If so, provide the name of the MS4 owner. The owner of the facility shall notify the MS4 owner in writing of the existence of the discharge within 30 days of coverage under the general permit and shall copy the DEQ regional office with the notification. The notification shall include the following information: the name of the facility, a contact person and phone number, the location of the discharge, the nature of the discharge, and the facility's VPDES general permit number;

16. Indicate if there are vehicle or equipment degreasing activities performed on site. If yes, indicate if there is any process wastewater generated from these activities;

17. Monitoring data to determine compliance with 9VAC25-260-310 m (Chickahominy special standards) as per Part I B 14 of this permit;

18. Provide certification that the process water system is designed to operate as "no discharge" if special condition Part I B 17 is to apply to the facility. Identify the emergency outfall number; and

19. The following certification:

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system or those persons directly responsible for gathering the information, the information submitted is to the best of my knowledge and belief true, accurate, and complete. I am aware that there are significant penalties for submitting false information including the possibility of fine and imprisonment for knowing violations."

D. The registration statement shall be signed in accordance with 9VAC25-31-110.

E. Where to submit. The registration statement may be delivered to the department by either postal or electronic mail and shall be submitted to the DEQ regional office serving the area where the industrial facility is located.

9VAC25-190-65. (Repealed.)

9VAC25-190-70. General permit.

Any owner whose registration statement is accepted by the board will receive coverage under the following permit and shall comply with the requirements in it and be subject to all requirements of the VPDES permit regulation, 9VAC25-31.

General Permit No.: VAG84
 Effective date: July 1, 2014
 Expiration date: June 30, 2019

GENERAL PERMIT FOR NONMETALLIC MINERAL MINING

AUTHORIZATION TO DISCHARGE UNDER THE VIRGINIA POLLUTANT DISCHARGE
 ELIMINATION SYSTEM AND THE VIRGINIA STATE WATER CONTROL LAW

In compliance with the provisions of the Clean Water Act, as amended, and pursuant to the State Water Control Law and regulations adopted pursuant to it, owners of nonmetallic mineral mines are authorized to discharge to surface waters within the boundaries of the Commonwealth of Virginia, except those specifically named in board regulations that prohibit such discharges.

The authorized discharge shall be in accordance with this cover page, Part I - Effluent Limitations, Monitoring Requirements, and Special Conditions, Part II - Stormwater Management, and Part III - Conditions Applicable to All VPDES Permits, as set forth herein.

Part I

Effluent Limitations, Monitoring Requirements, and Special Conditions

A. Effluent limitations and monitoring requirements.

1. During the period beginning with the permittee's coverage under this general permit and lasting until the permit's expiration date, the permittee is authorized to discharge process wastewater and commingled stormwater associated with industrial activity from outfall(s).

Such discharges shall be limited and monitored by the permittee as specified below:

EFFLUENT CHARACTERISTICS	DISCHARGE LIMITATIONS			MONITORING REQUIREMENTS	
	Monthly Average	Daily Minimum	Daily Maximum	Frequency ⁽¹⁾	Sample Type
Flow (MGD)	NL	NA	NL	1/3 Months	Estimate
Total Suspended Solids (mg/l)	30	NA	60	1/3 Months	Grab
pH (standard units) ⁽²⁾	NA	6.0	9.0	1/3 Months	Grab
Total Petroleum Hydrocarbons (mg/l) ⁽³⁾	NA	NA	NL	1/3 Months	Grab

NL = No Limitation, monitoring required

NA = Not Applicable

⁽¹⁾Discharge Monitoring Reports (DMRs) of quarterly monitoring shall be submitted to the DEQ regional office no later than the 10th day of April, July, October, and January.

⁽²⁾Where the Water Quality Standards (9VAC25-260) establish alternate standards for pH, those standards shall be the minimum and maximum pH effluent limits.

⁽³⁾Monitoring for total petroleum hydrocarbons is only required for outfalls that contain process wastewater from vehicle or equipment degreasing activities. Total petroleum hydrocarbons shall be analyzed using EPA SW-846 Method 8015 B (1996), 8015C (2000), 8015C (2007), 8015 D (2003) for diesel range organics, or EPA 40 CFR 136.

2. During the period beginning with the permittee's coverage under the general permit and lasting until the permit's expiration date, the permittee is authorized to discharge stormwater associated with industrial activity that does not combine with other wastewaters prior to discharge from outfall(s).

Such discharges shall be limited and monitored by the permittee as specified below:

EFFLUENT CHARACTERISTICS	DISCHARGE LIMITATIONS			MONITORING REQUIREMENTS	
	Monthly Average	Daily Minimum	Daily Maximum	Frequency ⁽¹⁾	Sample Type
Flow (MG)	NA	NA	NL	1/Year	Estimate ⁽²⁾
Total Suspended Solids (mg/l)	NA	NA	NL ⁽³⁾	1/Year	Grab
pH (standard units)	NA	NL	NL	1/Year	Grab

NL = No Limitation, monitoring required

NA = Not applicable

⁽¹⁾Discharge Monitoring Reports (DMRs) of yearly monitoring (January 1 to December 31) shall be submitted to the DEQ regional office no later than the 10th day of January.

⁽²⁾ Estimate of the total volume of the discharge during the storm event.

⁽³⁾Refer to Part I B 12 should the TSS evaluation monitoring exceed 100 mg/l daily maximum.

B. Special conditions.

1. Vehicles and equipment utilized during the industrial activity on a site must be operated and maintained in such a manner as to prevent the potential or actual point source pollution of the surface or groundwaters of the state. Fuels, lubricants, coolants, and hydraulic fluids, or any other petroleum products, shall not be disposed of by discharging on the ground or into surface waters. Spent fluids shall be disposed of in a manner so as not to enter the surface or groundwaters of the state and in accordance with the applicable state and federal disposal regulations. Any spilled fluids shall be cleaned up and disposed of in a manner so as not to allow their entry into the surface or groundwaters of the state.

2. No sewage shall be discharged from this mineral mining activity except under the provisions of another VPDES permit specifically issued for that purpose.

3. There shall be no chemicals added to the discharge, other than those listed on the owner's approved registration statement.

4. The permittee shall submit a new registration statement if the mining permit approved by the Division of Mineral Mining (or associated waived program, or bordering state mine authority) is modified or reissued in any way that would affect the outfall location or the characteristics of a discharge covered by this general permit. Government owned and operated mines without mining permits shall submit the registration statement whenever outfall location or characteristics are altered. The new registration statement shall be filed within 30 days of the outfall relocation or change in the characteristics of the discharge.

5. The permittee shall notify the department as soon as they know or have reason to believe:

a. That any activity has occurred or will occur that would result in the discharge, on a routine or frequent basis, of any toxic pollutant that is not limited in this permit, if that discharge will exceed the highest of the following notification levels:

(1) One hundred micrograms per liter (100 µg/l);

(2) Two hundred micrograms per liter (200 µg/l) for acrolein and acrylonitrile; five hundred micrograms per liter (500 µg/l) for 2,4-dinitrophenol and for 2-methyl-4,6-dinitrophenol; and one milligram per liter (1 mg/l) for antimony;

(3) Five times the maximum concentration value reported for that pollutant in the permit application; or

(4) The level established by the board.

b. That any activity has occurred or will occur that would result in any discharge, on a nonroutine or infrequent basis, of a toxic pollutant that is not limited in this permit, if that discharge will exceed the highest of the following notification levels:

(1) Five hundred micrograms per liter (500 µg/l);

(2) One milligram per liter (1 mg/l) for antimony;

(3) Ten times the maximum concentration value reported for that pollutant in the permit application; or

(4) The level established by the board.

6. Except as expressly authorized by this permit, no product, materials, industrial wastes, or other wastes resulting from the purchase, sale, mining, extraction, transport, preparation, or storage of raw or intermediate materials, final product, by-product or wastes, shall be handled, disposed of, or stored so as to permit a discharge of such product, materials, industrial wastes, or other wastes to state waters.

7. There shall be no discharge of process wastewater pollutants from colocated asphalt paving materials operations. For the purposes of this special condition, process wastewater pollutants are any pollutants present in water used in asphalt paving materials manufacturing that come into direct contact with any raw materials, intermediate product, by-product or product related to the asphalt paving materials manufacturing process.

8. Process water may be used on site for the purpose of dust suppression. Dust suppression shall be carried out as a best management practice but not as a wastewater disposal method provided that ponding or direct run-off from the site does not occur during or immediately following its application.

9. Process water from mine dewatering may be provided to local property owners for beneficial agricultural use.

10. There shall be no discharge of floating solids or visible foam in other than trace amounts from process water discharges. There shall be no solids deposition or oil sheen from petroleum products discharged to surface water as a result of the industrial activity.

11. The permittee shall report at least two significant digits for a given parameter. Regardless of the rounding convention used (i.e., five always rounding up or to the nearest even number) by the permittee, the permittee shall use the convention consistently and shall ensure that consulting laboratories employed by the permittee use the same convention.

12. Stormwater monitoring total suspended solids (TSS) evaluation. Permittees that monitor stormwater associated with industrial activity that does not combine with other wastewaters prior to discharge shall review the results of the TSS monitoring required by Part I A 2 to determine if changes to the stormwater pollution prevention plan (SWPPP)

may be necessary. If the TSS monitoring results are greater than the evaluation value of 100 mg/l, then the permittee shall perform the inspection and maintain documentation as described in Part II H 3 d for that outfall. Any deficiencies noted during the inspection shall be corrected in a timely manner.

13. Discharges to waters subject to TMDL wasteload allocations. Owners of facilities that are a source of the specified pollutant of concern to waters for which a total maximum daily load (TMDL) wasteload allocation has been approved prior to the term of this permit shall incorporate measures and controls into the SWPPP required by Part II that are consistent with the assumptions and requirements of the TMDL. The department will provide written notification to the owner that a facility is subject to the TMDL requirements. If the TMDL establishes a numeric wasteload allocation that applies to discharges from the facility, the owner shall perform any required monitoring in accordance with Part I A and implement measures necessary to meet that allocation.

14. Discharges in the entire Chickahominy watershed above Walker's Dam (excluding discharges consisting solely of stormwater) shall also meet the effluent limitations in 9VAC25-260-310 m (special standards and requirements) of the January 6, 2011, water quality standards regulation. These limitations are BOD₅ (6.0 mg/l average and 8.0 mg/l maximum), total suspended solids (TSS) (5.0 mg/l average and 7.5 mg/l maximum), total phosphorus (0.10 mg/l average), ammonia as nitrogen (2.0 mg/l average), and settleable solids (0.1 mg/l average). These parameters, except for TSS, shall be monitored once per calendar year and the data submitted with the next registration statement (for the 2019 reissuance). TSS data shall be monitored and submitted with the Part I A DMR.

15. The discharges authorized by this permit shall be controlled as necessary to meet applicable water quality standards.

16. Inactive and unstaffed facilities (including temporarily inactive sites).

a. A waiver of the process and stormwater monitoring and routine inspections may be exercised by the board at a facility that is both inactive and unstaffed as long as the facility remains inactive and unstaffed. Such a facility is required to conduct an annual comprehensive site inspection in accordance with the requirements in Part II H 4. No DMR reports will be required to be submitted when a facility is approved as inactive and unstaffed.

b. An inactive and unstaffed sites waiver request shall be submitted to the board for approval and shall include the name of the facility; the facility's VPDES general permit registration number; a contact person, phone number, and email address (if available); the reason for the request; and the date the facility became or will become inactive and unstaffed. The waiver request shall be signed and certified in accordance with Part III K. If this waiver is granted, a copy of the request and the board's written approval of the waiver shall be maintained with the SWPPP.

c. To reactivate the site the permittee shall notify the department within 30 days or an alternate timeframe if written approval is received in advance from the board, and all process and stormwater monitoring and routine inspections shall be resumed immediately. This notification must be submitted to the department, signed in accordance with Part III K, and retained on site at the facility covered by this permit in accordance with Part III B.

d. The board retains the authority to revoke this waiver when it is determined that the discharge causes, has a reasonable potential to cause, or contributes to a water quality standards violation.

17. Process water systems designed to operate as "no discharge" shall have no discharge of wastewater or pollutants, except in storm events greater than a 25-year, 24-

hour storm event. In the event of such a discharge, the permittee shall report an unusual or extraordinary discharge per Part III H of this permit. No sampling or DMR is required for these discharges as they are considered to be discharging in emergency discharge conditions. These discharges shall not contravene the Water Quality Standards (9VAC25-260), as adopted and amended by the board, or any provision of the State Water Control Law. Any other discharge from this type of system is prohibited, and shall be reported as an unauthorized discharge per Part III G of this permit.

18. Notice of termination.

a. The owner may terminate coverage under this general permit by filing a complete notice of termination. The notice of termination may be filed after one or more of the following conditions have been met:

- (1) Operations have ceased at the facility and there are no longer discharges of process wastewater or stormwater associated with the industrial activity;
- (2) A new owner has assumed responsibility for the facility (NOTE: A notice of termination does not have to be submitted if a VPDES Change of Ownership Agreement Form has been submitted);
- (3) All discharges associated with this facility have been covered by an individual VPDES permit or an alternative VPDES permit; or
- (4) Termination of coverage is being requested for another reason, provided the board agrees that coverage under this general permit is no longer needed.

b. The notice of termination shall contain the following information:

- (1) Owner's name, mailing address, telephone number, and email address (if available);
- (2) Facility name and location;
- (3) VPDES general permit registration number for the facility; and
- (4) The basis for submitting the notice of termination, including:
 - (a) A statement indicating that a new owner has assumed responsibility for the facility;
 - (b) A statement indicating that operations have ceased at the facility, a closure plan has been implemented according to the O & M Manual, and there are no longer discharges from the facility;
 - (c) A statement indicating that all discharges have been covered by an individual VPDES permit; or
 - (d) A statement indicating that termination of coverage is being requested for another reason (state the reason).

c. The following certification:

"I certify under penalty of law that all wastewater and stormwater discharges from the identified facility that are authorized by this VPDES general permit have been eliminated, or covered under a VPDES individual or alternative permit, or that I am no longer the owner of the facility, or permit coverage should be terminated for another reason listed above. I understand that by submitting this notice of termination, that I am no longer authorized to discharge nonmetallic mineral mining wastewater or stormwater in accordance with the general permit, and that discharging pollutants to surface waters is unlawful where the discharge is not authorized by a VPDES permit. I also understand that the submittal of this notice of termination does not release an owner from liability for any violations of this permit or the Clean Water Act."

d. The notice of termination shall be submitted to the department and signed in accordance with Part III K.

Part II
Stormwater Management

A. Monitoring instructions.

1. Collection and analysis of samples. Sampling requirements shall be assessed on an outfall-by-outfall basis. Samples shall be collected and analyzed in accordance with the requirements of Part III A.

2. When and how to sample.

a. In the case of snowmelt or a discharge from a stormwater management structure (a series of settling lagoons), a representative sample shall be taken at the time the discharge occurs.

b. For all other types of stormwater discharges, a minimum of one grab sample shall be taken resulting from a storm event that results in an actual discharge from the site (defined as a "measurable storm event"), providing the interval from the preceding measurable storm event is at least 72 hours. The 72-hour storm interval is waived if the permittee is able to document with the discharge monitoring report (DMR) that less than a 72-hour interval is representative for local storm events during the sampling period. The grab sample shall be taken during the first 30 minutes of the discharge. If it is not practicable to take the sample during the first 30 minutes, the sample may be taken during the first three hours of discharge provided that the permittee explains with the DMR why a grab sample during the first 30 minutes was impracticable.

B. Representative discharge. When a facility has two or more exclusively stormwater outfalls that the permittee reasonably believes discharge substantially identical effluents, based on a consideration of similarity of industrial activity, significant materials, and management practices and activities within the area drained by the outfalls, then the permittee may submit information with the registration statement substantiating the request for only one DMR to be issued for the outfall to be sampled that represents one or more substantially identical outfalls. Also the permittee must list on the DMR of the outfall to be sampled all outfall locations that are represented by the discharge.

C. Sampling waivers. When a permittee is unable to conduct stormwater monitoring within the specified sampling period due to no measurable storm event or adverse weather conditions, documentation shall be submitted explaining the permittee's inability to conduct the stormwater monitoring. The documentation must include the dates and times that the outfalls were viewed and sampling was attempted. Adverse weather conditions that may prohibit the collection of samples include weather conditions that create dangerous conditions for personnel (such as local flooding, high winds, hurricane, tornadoes, electrical storms, etc.). Acceptable documentation includes but is not limited to National Climatic Data Center weather station data, local weather station data, facility rainfall logs, and other appropriate supporting data. All documentation shall also be maintained with the SWPPP.

D. Stormwater pollution prevention plans (SWPPP). An SWPPP shall be developed and implemented for the facility. The plan shall include best management practices (BMPs) that are reasonable, economically practicable, and appropriate in light of current industry practices. The BMPs shall be selected, designed, installed, implemented, and maintained in accordance with good engineering practices to eliminate or reduce the pollutants in all stormwater discharges

from the facility. The SWPPP shall also include all control measures necessary for the stormwater discharges to meet applicable water quality standards.

The SWPPP requirements of this general permit may be fulfilled, in part, by incorporating by reference other plans or documents such as an erosion and sediment control plan, a mine drainage plan as required by the Virginia Division of Mineral Mining, a spill prevention control and countermeasure (SPCC) plan developed for the facility under § 311 of the federal Clean Water Act or BMP programs otherwise required for the facility provided that the incorporated plan meets or exceeds the plan requirements of Part II H (contents of plan). All plans incorporated by reference into the SWPPP become enforceable under this permit. If a plan incorporated by reference does not contain all of the required elements of Part II H, the permittee must develop the missing SWPPP elements and include them in the required plan.

E. Deadlines for plan preparation and compliance.

1. Owners of existing facilities that were covered under the 2009 Nonmetallic Mineral Mining General Permit that are continuing coverage under this general permit shall update and implement any revisions to the SWPPP within 90 days of the board granting coverage under this permit.
2. Owners of new facilities, facilities previously covered by an expiring individual permit, and existing facilities not currently covered by a VPDES permit that elect to be covered under this general permit shall prepare and implement the SWPPP prior to submitting the registration statement.
3. Where the owner of an existing facility that is covered by this permit changes, the new owner of the facility shall update and implement any revisions to the SWPPP within 60 days of ownership change.
4. Upon a showing of good cause, the director may establish a later date in writing for the preparation and compliance with the SWPPP.

F. Signature and plan review.

1. The SWPPP shall be signed in accordance with Part III K (signatory requirements), and be retained on site at the facility covered by this permit in accordance with Part III B (records) of this permit. When there are no on-site buildings or offices in which to store the plan, it shall be kept at the nearest company office.
2. The permittee shall make the SWPPP, annual site compliance inspection report, or other information available to the department upon request.
3. The director, or an authorized representative, may notify the permittee at any time that the SWPPP, BMPs, or other components of the facility's stormwater program do not meet one or more of the requirements of this part. Such notification shall identify specific provisions of the permit that are not being met and may include required modifications to the stormwater program, additional monitoring requirements, and special reporting requirements. Within 60 days of such notification from the director, or as otherwise provided by the director, or an authorized representative, the permittee shall make the required changes to the plan and shall submit to the department a written certification that the requested changes have been made.

G. Maintaining an updated SWPPP. The permittee shall review and amend the SWPPP as appropriate whenever:

1. There is construction or a change in design, operation, or maintenance that has a significant effect on the discharge or the potential for the discharge of pollutants to surface waters;
2. Routine inspections or compliance evaluations determine that there are deficiencies in the BMPs;

3. Inspections by local, state, or federal officials determine that modifications to the SWPPP are necessary;
4. There is a spill, leak, or other release at the facility; or
5. There is an unauthorized discharge from the facility.

SWPPP modifications shall be made within 30 calendar days after discovery, observation, or an event requiring an SWPPP modification. Implementation of new or modified BMPs (distinct from regular preventive maintenance of existing BMPs described in Part II H 3 b (preventative maintenance) shall be initiated before the next storm event if possible, but no later than 60 days after discovery, or as otherwise provided or approved by the director. The amount of time taken to modify a BMP or implement additional BMPs shall be documented in the SWPPP.

If the SWPPP modification is based on a release or unauthorized discharge, include a description and date of the release, the circumstances leading to the release, actions taken in response to the release, and measures to prevent the recurrence of such releases. Unauthorized releases and discharges are subject to the reporting requirements of Part III G of this permit.

H. Contents of plan. The plan shall include, at a minimum, the following items:

1. Pollution prevention team. Each plan shall identify the staff individuals by name or title who comprise the facility's stormwater pollution prevention team. The pollution prevention team is responsible for assisting the facility or plant manager in developing, implementing, maintaining, revising, and ensuring compliance with the facility's SWPPP. Specific responsibilities of each staff individual on the team shall be identified and listed.

2. Summary of potential pollutant sources. The plan shall identify where industrial materials or activities at the facility are exposed to stormwater. The description shall include:

- a. Site map. The site map shall document:

- (1) An outline of the drainage area of each stormwater outfall that are within the facility boundaries, each existing structural control measure to reduce pollutants in stormwater run-off, surface water bodies, locations where materials are exposed to precipitation, locations where major spills or leaks identified under Part II H 2 c (spills and leaks) of this permit have occurred, and the locations of the following activities where such activities are exposed to precipitation: fueling stations, vehicle or equipment degreasing, cleaning areas, loading/unloading areas, locations used for the treatment, storage or disposal of wastes and wastewaters, liquid storage tanks, processing areas and storage areas. The map must indicate all outfall locations. The types of discharges contained in the drainage areas of the outfalls must be indicated either on the map or in an attached narrative.

- (2) For each area of the facility that generates stormwater discharges associated with industrial activity with a potential for containing significant amounts of pollutants, locations of stormwater conveyances, including ditches, pipes, swales, and inlets, and the directions of stormwater flow and an identification of the types of pollutants that are likely to be present in stormwater discharges associated with industrial activity. Factors to consider include the toxicity of the chemicals; quantity of chemicals used, produced or discharged; the likelihood of contact with stormwater; and history of significant spills or leaks of toxic or hazardous pollutants. Flows with a potential for causing erosion shall be identified.

- b. Inventory of exposed materials. A list of the industrial materials or activities, including but not limited to material handling equipment or activities, industrial machinery, raw materials, industrial production and processes, intermediate

products, by-products, final products, and waste products. Material handling activities include but are not limited to the storage, loading and unloading, transportation, disposal, or conveyance of any raw material, intermediate product, final product, or waste product.

c. Spills and leaks. A list of significant spills and leaks of toxic or hazardous pollutants that occurred at areas that are exposed to precipitation or that otherwise drain to a stormwater conveyance at the facility after the date of three years prior to the date of coverage under this general permit. Such list shall be updated as appropriate during the term of the permit.

d. Sampling data. A summary of existing stormwater sampling data taken at the facility. The summary shall include, at a minimum, any data collected during the previous three years.

3. Stormwater controls. BMPs shall be implemented for all areas identified in Part II H 2 b (inventory of exposed materials) to prevent or control pollutants in stormwater discharges from the facility. All reasonable steps shall be taken to control or address the quality of discharges from the site that may not originate at the facility. The SWPPP shall describe the type, location, and implementation of all BMPs for each area where industrial materials or activities are exposed to stormwater. The BMPs shall also address the following minimum components, including a schedule for implementing such controls:

a. Good housekeeping. Good housekeeping requires the maintenance of areas that may contribute pollutants to stormwater discharges in a clean, orderly manner. The plan shall describe procedures performed to minimize contact of materials with stormwater run-off. Particular attention should be paid to areas where raw materials are stockpiled, material handling areas, storage areas, liquid storage tanks, vehicle fueling and maintenance areas, and loading/unloading areas.

b. Preventive maintenance. A preventive maintenance program shall involve regular inspection, testing, maintenance, and repairing of all industrial equipment and systems to avoid breakdowns or failures that could result in leaks, spills, and other releases. All BMPs identified in the SWPPP shall be maintained in effective operating condition. The SWPPP shall include a description of procedures and a regular schedule for preventive maintenance and observation of all BMPs and shall include a description of the back-up practices that are in place should a run-off event occur while a BMP is off line or not operating effectively. The effectiveness of nonstructural BMPs shall also be maintained by appropriate means (e.g., spill response supplies available and personnel trained). If site inspections required by Part II H 3 d (routine facility inspections) or Part II H 4 (comprehensive site compliance evaluation) identify BMPs that are not operating effectively, repairs or maintenance shall be performed before the next anticipated storm event. If maintenance prior to the next anticipated storm event is not possible, maintenance shall be scheduled and accomplished as soon as practicable. Documentation shall be kept with the SWPPP of maintenance and repairs of BMPs, including the date(s) of regular maintenance, date(s) of discovery of areas in need of repair or replacement, date(s) for repairs, date(s) that the BMP(s) returned to full function, and the justification for an extended maintenance or repair schedules. The maintenance program shall require periodic removal of debris from discharge diversions and conveyance systems. Permittees using settling basins to control their effluents must provide maintenance schedules for such basins in the pollution prevention plan.

c. Spill prevention and response procedures. The plan shall describe the procedures that will be followed for preventing and responding to spills and leaks, including barriers between material storage and traffic areas, secondary containment provisions, procedures for material storage and handling, response procedures for notification of appropriate facility personnel, emergency agencies, and regulatory agencies and procedures for stopping, containing, and cleaning up spills. Measures for cleaning up hazardous material spills or leaks shall be consistent with applicable RCRA regulations at 40 CFR Part 264 and 40 CFR Part 265. Employees who may cause, detect, or respond to a spill or leak shall be trained in these procedures and have necessary spill response equipment available. If possible, one of these individuals shall be a member of the pollution prevention team. Contact information for individuals and agencies that must be notified in the event of a spill shall be included in the SWPPP and in other locations where it will be readily available.

d. Routine facility inspections.

(1) Facility personnel who are familiar with the mining activity, the best management practices and the stormwater pollution prevention plan shall be identified to inspect material storage and handling areas, including but not limited to areas where aggregate is stockpiled outdoors, liquid storage tanks, hoppers or silos, material handling vehicles, equipment, and processing areas; to inspect vehicle and equipment maintenance areas and cleaning and fueling areas; to inspect best management practices; and to conduct visual examinations of stormwater associated with industrial activity.

(2) The inspection frequency shall be specified in the plan based upon a consideration of the level of industrial activity at the facility, but shall be a minimum of quarterly. Inspections of best management practices shall include inspection of stormwater discharge diversions, conveyance systems, sediment control and collection systems, containment structures, vegetation, serrated slopes, and benched slopes to determine their effectiveness, the integrity of control structures, if soil erosion has occurred, or if there is evidence of actual or potential discharge of contaminated stormwater.

(3) Quarterly visual examinations of stormwater discharges associated with industrial activity shall include examination of stormwater samples representative of storm event discharges from the facility and observation of color, odor, clarity, floating solids, settled solids, suspended solids, foam, oil sheen, and other obvious indicators of stormwater pollution.

(4) Site inspection, best management practices inspection and visual examination results must be documented and maintained on-site with the SWPPP. Documentation for visual examinations of stormwater shall include the examination date and time, examination personnel, outfall location, the nature of the discharge, visual quality of the stormwater discharge and probable sources of any observed stormwater contamination. Part II A regarding monitoring instructions, Part II B regarding representative discharges, and Part II C regarding sampling waivers shall apply to the taking of samples for visual examination except that (i) the documentation required by these sections shall be retained with the SWPPP visual examination records rather than submitted to the department, and (ii) substitute sampling for waived sampling is not required if the proper documentation is maintained.

(5) A set of tracking or followup procedures shall be used to ensure that appropriate actions are taken in response to the inspections.

- e. Employee training. Employee training programs shall inform personnel responsible for implementing activities identified in the stormwater pollution prevention plan or otherwise responsible for stormwater management at all levels of responsibility of the components and goals of the stormwater pollution prevention plan. Training should address topics such as spill response, good housekeeping and material management practices. A pollution prevention plan shall identify periodic dates for such training.
 - f. Recordkeeping and internal reporting procedures. A description of incidents such as spills, or other discharges, along with other information describing the quality and quantity of stormwater discharges shall be included in the plan required under this part. Inspections and maintenance activities shall be documented and records of such activities shall be incorporated into the plan. Ineffective best management practices must be recorded and the date of their corrective action noted.
 - g. Sediment and erosion control. The plan shall identify areas that, due to topography, land disturbance (e.g., construction, landscaping, site grading), or other factors, have a potential for soil erosion. The permittee shall identify and implement structural, vegetative, or stabilization BMPs to prevent or control on-site and off-site erosion and sedimentation.
 - h. Management of run-off. The plan shall describe the stormwater run-off management practices (i.e., permanent structural BMPs) for the facility. These types of BMPs are typically used to divert, infiltrate, reuse, or otherwise reduce pollutants in stormwater discharges from the site. Appropriate measures may include: vegetative swales and practices, reuse of collected stormwater (such as for a process or as an irrigation source), inlet controls (such as oil/water separators), snow management activities, infiltration devices, and wet detention/retention devices.
4. Comprehensive site compliance evaluation. Facility personnel who are familiar with the mining activity, the BMPs, and the SWPPP shall conduct site compliance evaluations at appropriate intervals specified in the plan, but in no case less frequently than once a year. Evaluations shall include all areas where industrial materials or activities are exposed to stormwater as identified in Part II H 2 b (inventory exposed materials). Such evaluations shall include the following:
- a. Areas contributing to a stormwater discharge associated with industrial activity, including material storage and handling areas (e.g., areas where aggregate is stockpiled outdoors, liquid storage tanks, hoppers or silos, material handling vehicles, equipment, and processing areas); vehicle and equipment maintenance areas and cleaning and fueling areas; off-site tracking of industrial or waste materials or sediment where vehicles enter or exit the site; tracking or blowing of raw, final, or waste materials from areas of no exposure to exposed areas; and residue or trash shall be visually inspected for evidence of, or the potential for, pollutants entering the drainage system. Measures to reduce pollutant loadings shall be evaluated to determine whether they are adequate and properly implemented in accordance with the terms of the permit or whether additional control measures are needed. Structural stormwater management measures, sediment and erosion control measures, and other structural pollution prevention measures identified in the plan shall be observed to ensure that they are operating correctly. A visual inspection of equipment needed to implement the plan, such as spill response equipment, shall be made. A review of training performed, routine inspections completed, visual examinations completed, maintenance performed, and effective operation of BMPs, shall be made.

b. Based on the results of the evaluation, the summary of potential pollutant sources identified in the plan in accordance with Part II H 2 (summary of potential pollutant sources) of this permit and pollution prevention measures and controls identified in the plan in accordance with Part II H 3 (stormwater controls) of this permit shall be revised as appropriate within 14 days of such inspection and shall provide for implementation of any changes to the plan in a timely manner, but in no case more than 90 days after the inspection.

c. A report summarizing the scope of the inspection, personnel making the inspection, the dates of the inspection, observations relating to the implementation of the SWPPP, including the elements stipulated in Part II H 4 a, and actions taken in accordance with Part II H 4 b of this permit shall be made and retained as required in Part III B (records). The report shall identify any incidents of noncompliance. Where a report does not identify any incidents of noncompliance, the report shall contain a certification that the facility is in compliance with the SWPPP and this permit. The report shall be signed in accordance with Part III K (signatory requirements) of this permit and retained as required in Part III B.

d. Where compliance evaluation schedules overlap with inspections required under Part II H 3 d (inspections), the compliance evaluation may be conducted in place of one such inspection.

Part III

Conditions Applicable to All VPDES Permits

A. Monitoring.

1. Samples and measurements taken as required by this permit shall be representative of the monitored activity.
2. Monitoring shall be conducted according to procedures approved under 40 CFR Part 136 or alternative methods approved by the U.S. Environmental Protection Agency, unless other procedures have been specified in this permit.
3. The permittee shall periodically calibrate and perform maintenance procedures on all monitoring and analytical instrumentation at intervals that will ensure accuracy of measurements.
4. Samples taken as required by this permit shall be analyzed in accordance with 1VAC30-45, Certification for Noncommercial Environmental Laboratories, or 1VAC30-46, Accreditation for Commercial Environmental Laboratories.

B. Records.

1. Records of monitoring information shall include:
 - a. The date, exact place, and time of sampling or measurements;
 - b. The individual(s) who performed the sampling or measurements;
 - c. The date(s) and time(s) analyses were performed;
 - d. The individual(s) who performed the analyses;
 - e. The analytical techniques or methods used; and
 - f. The results of such analyses.
2. The permittee shall retain records of all monitoring information, including all calibration and maintenance records and all original strip chart recordings for continuous monitoring instrumentation, copies of all reports required by this permit, and records of all data used to complete the registration statement for this permit, for a period of at least three years from the date of the sample, measurement, report or request for coverage. This period of retention shall be extended automatically during the course of any unresolved litigation

regarding the regulated activity or regarding control standards applicable to the permittee, or as requested by the board.

C. Reporting monitoring results.

1. The permittee shall submit the results of the monitoring required by this permit not later than the 10th day of the month after monitoring takes place, unless another reporting schedule is specified elsewhere in this permit. Monitoring results shall be submitted to the department's regional office.
2. Monitoring results shall be reported on a discharge monitoring report (DMR) or on forms provided, approved or specified by the department.
3. If the permittee monitors any pollutant specifically addressed by this permit more frequently than required by this permit using test procedures approved under 40 CFR Part 136 or using other test procedures approved by the U.S. Environmental Protection Agency or using procedures specified in this permit, the results of this monitoring shall be included in the calculation and reporting of the data submitted in the DMR or reporting form specified by the department.
4. Calculations for all limitations that require averaging of measurements shall utilize an arithmetic mean unless otherwise specified in this permit.

D. Duty to provide information. The permittee shall furnish to the department, within a reasonable time, any information that the board may request to determine whether cause exists for modifying, revoking and reissuing, or terminating coverage under this permit or to determine compliance with this permit. The board may require the permittee to furnish, upon request, such plans, specifications, and other pertinent information as may be necessary to determine the effect of the wastes from its discharge on the quality of state waters, or such other information as may be necessary to accomplish the purposes of the State Water Control Law. The permittee shall also furnish to the department, upon request, copies of records required to be kept by this permit.

E. Compliance schedule reports. Reports of compliance or noncompliance with, or any progress reports on, interim and final requirements contained in any compliance schedule of this permit shall be submitted no later than 14 days following each schedule date.

F. Unauthorized discharges. Except in compliance with this permit or another permit issued by the board, it shall be unlawful for any person to:

1. Discharge into state waters sewage, industrial wastes, other wastes, or any noxious or deleterious substances; or
2. Otherwise alter the physical, chemical or biological properties of such state waters and make them detrimental to the public health, or to animal or aquatic life, or to the use of such waters for domestic or industrial consumption, or for recreation, or for other uses.

G. Reports of unauthorized discharges. Any permittee who discharges or causes or allows a discharge of sewage, industrial waste, other wastes or any noxious or deleterious substance into or upon state waters in violation of Part III F (unauthorized discharges); or who discharges or causes or allows a discharge that may reasonably be expected to enter state waters in violation of Part III F, shall notify the department of the discharge immediately upon discovery of the discharge, but in no case later than 24 hours after said discovery. A written report of the unauthorized discharge shall be submitted to the department within five days of discovery of the discharge. The written report shall contain:

1. A description of the nature and location of the discharge;
2. The cause of the discharge;

3. The date on which the discharge occurred;
4. The length of time that the discharge continued;
5. The volume of the discharge;
6. If the discharge is continuing, how long it is expected to continue;
7. If the discharge is continuing, what the expected total volume of the discharge will be; and
8. Any steps planned or taken to reduce, eliminate and prevent a recurrence of the present discharge or any future discharges not authorized by this permit.

Discharges reportable to the department under the immediate reporting requirements of other regulations are exempted from this requirement.

H. Reports of unusual or extraordinary discharges. If any unusual or extraordinary discharge including a bypass or upset should occur from a treatment works and the discharge enters or could be expected to enter state waters, the permittee shall promptly notify (see NOTE in Part III I), in no case later than 24 hours, the department after the discovery of the discharge. This notification shall provide all available details of the incident, including any adverse effects on aquatic life and the known number of fish killed. The permittee shall reduce the report to writing and shall submit it to the department within five days of discovery of the discharge in accordance with Part III I 2. Unusual and extraordinary discharges include but are not limited to any discharge resulting from:

1. Unusual spillage of materials resulting directly or indirectly from processing operations;
2. Breakdown of processing or accessory equipment;
3. Failure or taking out of service some or all of the treatment works; and
4. Flooding or other acts of nature.

I. Reports of noncompliance. The permittee shall report any noncompliance that may adversely affect state waters or may endanger public health.

1. An oral report shall be provided within 24 hours from the time the permittee becomes aware of the circumstances. The following shall be included as information that shall be reported within 24 hours under this subdivision:

- a. Any unanticipated bypass; and
- b. Any upset that causes a discharge to surface waters.

2. A written report shall be submitted within five days and shall contain:

- a. A description of the noncompliance and its cause;
- b. The period of noncompliance, including exact dates and times, and if the noncompliance has not been corrected, the anticipated time it is expected to continue; and
- c. Steps taken or planned to reduce, eliminate, and prevent reoccurrence of the noncompliance.

The board may waive the written report on a case-by-case basis for reports of noncompliance under Part III I if the oral report has been received within 24 hours and no adverse impact on state waters has been reported.

3. The permittee shall report all instances of noncompliance not reported under Parts III I 1 or 2, in writing, at the time the next monitoring reports are submitted. The reports shall contain the information listed in Part III I 2.

NOTE: The immediate (within 24 hours) reports required in Parts III G, H and I may be made to the department's regional office. Reports may be made by telephone, FAX, or online at

<http://www.deq.virginia.gov/Programs/PollutionResponsePreparedness/MakingaReport.aspx>. For reports outside normal working hours, leave a message and this shall fulfill the immediate reporting requirement. For emergencies, the Virginia Department of Emergency Services maintains a 24-hour telephone service at 1-800-468-8892.

J. Notice of planned changes.

1. The permittee shall give notice to the department as soon as possible of any planned physical alterations or additions to the permitted facility. Notice is required only when:

a. The permittee plans alteration or addition to any building, structure, facility, or installation from which there is or may be a discharge of pollutants, the construction of which commenced:

(1) After promulgation of standards of performance under § 306 of the federal Clean Water Act that are applicable to such source; or

(2) After proposal of standards of performance in accordance with § 306 of the federal Clean Water Act that are applicable to such source, but only if the standards are promulgated in accordance with § 306 within 120 days of their proposal;

b. The alteration or addition could significantly change the nature or increase the quantity of pollutants discharged. This notification applies to pollutants that are subject neither to effluent limitations nor to notification requirements specified elsewhere in this permit; or

c. The alteration or addition results in a significant change in the permittee's sludge use or disposal practices and such alteration, addition, or change may justify the application of permit conditions that are different from or absent in the existing permit, including notification of additional use or disposal sites not reported during the permit application process or not reported pursuant to an approved land application plan.

2. The permittee shall give advance notice to the department of any planned changes in the permitted facility or activity that may result in noncompliance with permit requirements.

K. Signatory requirements.

1. Registration statement. All registration statements shall be signed as follows:

a. For a corporation: by a responsible corporate officer. For the purposes of this section, a responsible corporate officer means: (i) a president, secretary, treasurer, or vice-president of the corporation in charge of a principal business function, or any other person who performs similar policy-making or decision-making functions for the corporation, or (ii) the manager of one or more manufacturing, production, or operating facilities provided the manager is authorized to make management decisions that govern the operation of the regulated facility including having the explicit or implicit duty of making capital investment recommendations, and initiating and directing other comprehensive measures to assure long-term environmental compliance with environmental laws and regulations; the manager can ensure that the necessary systems are established or actions taken to gather complete and accurate information for permit application requirements; and where authority to sign documents has been assigned or delegated to the manager in accordance with corporate procedures;

b. For a partnership or sole proprietorship: by a general partner or the proprietor, respectively; or

c. For a municipality, state, federal, or other public agency: by either a principal executive officer or ranking elected official. For purposes of this section, a principal

executive officer of a public agency includes: (i) the chief executive officer of the agency or (ii) a senior executive officer having responsibility for the overall operations of a principal geographic unit of the agency.

2. Reports, etc. All reports required by permits, and other information requested by the board, shall be signed by a person described in Part III K 1 or by a duly authorized representative of that person. A person is a duly authorized representative only if:

- a. The authorization is made in writing by a person described in Part III K 1;
- b. The authorization specifies either an individual or a position having responsibility for the overall operation of the regulated facility or activity such as the position of plant manager, operator of a well or a well field, superintendent, position of equivalent responsibility, or an individual or position having overall responsibility for environmental matters for the company. A duly authorized representative may thus be either a named individual or any individual occupying a named position; and
- c. The written authorization is submitted to the department.

3. Changes to authorization. If an authorization under Part III K 2 is no longer accurate because a different individual or position has responsibility for the overall operation of the facility, a new authorization satisfying the requirements of Part III K 2 shall be submitted to the department prior to or together with any reports or information to be signed by an authorized representative.

4. Certification. Any person signing a document under Part III K 1 or 2 shall make the following certification:

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."

L. Duty to comply. The permittee shall comply with all conditions of this permit. Any permit noncompliance constitutes a violation of the State Water Control Law and the federal Clean Water Act, except that noncompliance with certain provisions of this permit may constitute a violation of the State Water Control Law but not the federal Clean Water Act. Permit noncompliance is grounds for enforcement action; for permit termination, revocation and reissuance, or modification; or denial of permit coverage.

M. Duty to reapply. If the permittee wishes to continue an activity regulated by this permit after the expiration date of this permit, the permittee shall submit a new registration statement at least 210 days before the expiration date of the existing permit, unless permission for a later date has been granted by the board. The board shall not grant permission for registration statements to be submitted later than the expiration date of the existing permit.

N. Effect of a permit. This permit does not convey any property rights in either real or personal property or any exclusive privileges, nor does it authorize any injury to private property or invasion of personal rights or any infringement of federal, state or local laws or regulations.

O. State law. Nothing in this permit shall be construed to preclude the institution of any legal action under, or relieve the permittee from any responsibilities, liabilities, or penalties established pursuant to, any other state law or regulation or under authority preserved by § 510 of the federal Clean Water Act. Except as provided in permit conditions on "bypass" (Part III U)

and "upset" (Part III V), nothing in this permit shall be construed to relieve the permittee from civil and criminal penalties for noncompliance.

P. Oil and hazardous substance liability. Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities, or penalties to which the permittee is or may be subject under §§ 62.1-44.34:14 through 62.1-44.34:23 of the State Water Control Law.

Q. Proper operation and maintenance. The permittee shall at all times properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) that are installed or used by the permittee to achieve compliance with the conditions of this permit. Proper operation and maintenance also includes effective plant performance, adequate funding, adequate staffing, and adequate laboratory and process controls, including appropriate quality assurance procedures. This provision requires the operation of back-up or auxiliary facilities or similar systems that are installed by the permittee only when the operation is necessary to achieve compliance with the conditions of this permit.

R. Disposal of solids or sludges. Solids, sludges or other pollutants removed in the course of treatment or management of pollutants shall be disposed of in a manner so as to prevent any pollutant from such materials from entering state waters.

S. Duty to mitigate. The permittee shall take all reasonable steps to minimize or prevent any discharge or sludge use or disposal in violation of this permit that has a reasonable likelihood of adversely affecting human health or the environment.

T. Need to halt or reduce activity not a defense. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

U. Bypass.

1. "Bypass" means the intentional diversion of waste streams from any portion of a treatment facility. The permittee may allow any bypass to occur that does not cause effluent limitations to be exceeded, but only if it also is for essential maintenance to ensure efficient operation. These bypasses are not subject to the provisions of Parts III U 2 and U 3.

2. Notice.

a. Anticipated bypass. If the permittee knows in advance of the need for a bypass, prior notice shall be submitted if possible at least 10 days before the date of the bypass.

b. Unanticipated bypass. The permittee shall submit notice of an unanticipated bypass as required in Part III I (reports of noncompliance).

3. Prohibition of bypass.

a. Bypass is prohibited, and the board may take enforcement action against a permittee for bypass, unless:

(1) Bypass was unavoidable to prevent loss of life, personal injury, or severe property damage;

(2) There were no feasible alternatives to the bypass, such as the use of auxiliary treatment facilities, retention of untreated wastes, or maintenance during normal periods of equipment downtime. This condition is not satisfied if adequate back-up equipment should have been installed in the exercise of reasonable engineering judgment to prevent a bypass that occurred during normal periods of equipment downtime or preventive maintenance; and

(3) The permittee submitted notices as required under Part III U 2.

- b. The board may approve an anticipated bypass, after considering its adverse effects, if the board determines that it will meet the three conditions listed in Part III U 3 a.

V. Upset.

1. An upset constitutes an affirmative defense to an action brought for noncompliance with technology-based permit effluent limitations if the requirements of Part III V 2 are met. A determination made during administrative review of claims that noncompliance was caused by upset, and before an action for noncompliance, is not a final administrative action subject to judicial review.
2. A permittee who wishes to establish the affirmative defense of upset shall demonstrate, through properly signed, contemporaneous operating logs or other relevant evidence that:
 - a. An upset occurred and that the permittee can identify the cause(s) of the upset;
 - b. The permitted facility was at the time being properly operated;
 - c. The permittee submitted notice of the upset as required in Part III I; and
 - d. The permittee complied with any remedial measures required under Part III S.
3. In any enforcement proceeding, the permittee seeking to establish the occurrence of an upset has the burden of proof.

W. Inspection and entry. The permittee shall allow the director or an authorized representative, upon presentation of credentials and other documents as may be required by law, to:

1. Enter upon the permittee's premises where a regulated facility or activity is located or conducted or where records must be kept under the conditions of this permit;
2. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
3. Inspect at reasonable times any facilities, equipment (including monitoring and control equipment), practices, or operations regulated or required under this permit; and
4. Sample or monitor at reasonable times, for the purposes of ensuring permit compliance or as otherwise authorized by the federal Clean Water Act and the State Water Control Law, any substances or parameters at any location.

For purposes of this section, the time for inspection shall be deemed reasonable during regular business hours and whenever the facility is discharging. Nothing contained herein shall make an inspection unreasonable during an emergency.

X. Permit actions. Permits may be modified, revoked and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition.

Y. Transfer of permits. Permits are not transferable to any person except after notice to the department. Coverage under this permit may be automatically transferred to a new permittee if:

1. The current permittee notifies the department at least 30 days in advance of the proposed transfer of the title to the facility or property unless permission for a later date has been granted by the department;
2. The notice includes a written agreement between the existing and new permittees containing a specific date for transfer of permit responsibility, coverage, and liability between them; and

3. The board does not notify the existing permittee and the proposed new permittee of its intent to deny the permittee coverage under the permit. If this notice is not received, the transfer is effective on the date specified in the agreement mentioned in Part III Y 2.

Z. Severability. The provisions of this permit are severable, and if any provision of this permit or the application of any provision of this permit to any circumstance is held invalid, the application of such provision to other circumstances and the remainder of this permit shall not be affected thereby.

FORMS (9VAC25-190)

[Department of Environmental Quality Water Division Permit Application Fee \(rev. 5/13\)](#)

[Virginia Pollutant Discharge Elimination System Change of Ownership Agreement Form \(undated\)](#)

Virginia Pollutant Discharge Elimination System General Permit Registration Statement -
Nonmetallic Mineral Mining