



COMMONWEALTH of VIRGINIA

DEPARTMENT OF ENVIRONMENTAL QUALITY

TIDEWATER REGIONAL OFFICE

5636 Southern Boulevard, Virginia Beach, Virginia 23462

(757) 518-2000 Fax (757) 518-2009

www.deq.virginia.gov

Doug Domenech
Secretary of Natural Resources

David K. Paylor
Director

Maria R. Nold
Regional Director

September 10, 2012

Mr. George C. Lyon, Jr.
President
Lyon Shipyard, Inc.
PO Box 2180
Norfolk, Virginia 23501

Location: Norfolk
Registration No.: 61274
AFS Id. No.: 51-710-00249

Dear Mr. Lyon:

Attached is a permit to operate a ship repair facility pursuant to 9 VAC 5 Chapter 80 of the Virginia Regulations for the Control and Abatement of Air Pollution. This permit incorporates provisions from the permit dated July 20, 2010.

The permit contains legally enforceable conditions. Failure to comply may result in a Notice of Violation and civil penalty. Please read all permit conditions carefully.

In evaluating the application and arriving at a final decision to issue this permit, the Department deemed the application complete on May 10, 2012 and solicited written public comments by placing a newspaper advertisement in the Virginian-Pilot on Wednesday, July 25, 2012. The thirty day comment period (provided for in 9 VAC 5-80-270) expired on Friday, August 24, 2012 with no comments having been received in this office.

This approval to operate does not relieve Lyon Shipyard, Inc. of the responsibility to comply with all other local, state, and federal permit regulations.

Issuance of this permit is a case decision. The Regulations, at 9 VAC 5-170-200, provide that you may request a formal hearing from this case decision by filing a petition with the Board within 30 days after this permit is mailed or delivered to you. Please consult that and other relevant provisions for additional requirements for such requests.

Additionally, as provided by Rule 2A:2 of the Supreme Court of Virginia, you have 30 days from the date you actually received this permit or the date on which it was mailed to you, whichever occurred first, within which to initiate an appeal to court by filing a Notice of Appeal with:

David K. Paylor, Director
Department of Environmental Quality
PO Box 1105
Richmond, VA 23218-1105

In the event that you receive this permit by mail, three days are added to the period in which to file an appeal. Please refer to Rule 2A of the Rules of the Supreme Court of Virginia for additional information including filing dates and the required content of the Notice of Appeal.

If you have any questions concerning this permit, please contact Cindy Keltner by phone at (757) 518-2167 or by e-mail at Cindy.Keltner@deq.virginia.gov.

Sincerely,

Troy D. Breathwaite
Regional Air Permits Manager

TDB/CLK/61274_003_12_T5new_FOP_cvrltr_LyonShipyardInc.docx

Attachment: Permit

cc: Manager, Data Analysis (electronic file submission)
Chief, Air Enforcement Branch (3AP13), U.S. EPA, Region III (electronic file submission)
Manager / Inspector, Air Compliance



COMMONWEALTH of VIRGINIA

DEPARTMENT OF ENVIRONMENTAL QUALITY

TIDEWATER REGIONAL OFFICE

5636 Southern Boulevard, Virginia Beach, Virginia 23462

(757) 518-2000 Fax (757) 518-2009

www.deq.virginia.gov

Doug Domenech
Secretary of Natural Resources

David K. Paylor
Director

Maria R. Nold
Regional Director

Federal Operating Permit Article 1

This permit is based upon the requirements of Title V of the Federal Clean Air Act and Chapter 80, Article 1, of the Commonwealth of Virginia Regulations for the Control and Abatement of Air Pollution. Until such time as this permit is reopened and revised, modified, revoked, terminated, or expires, the permittee is authorized to operate in accordance with the terms and conditions contained herein. This permit is issued under the authority of Title 10.1, Chapter 13, §10.1-1322 of the Air Pollution Control Law of Virginia. This permit is issued consistent with the Administrative Process Act, and 9 VAC 5-80-50 through 9 VAC 5-80-300, of the State Air Pollution Control Board Regulations for the Control and Abatement of Air Pollution of the Commonwealth of Virginia.

Authorization to operate a Stationary Source of Air Pollution as described in this permit is hereby granted to:

Permittee Name: Lyon Shipyard, Inc.
Facility Name: Lyon Shipyard, Inc.
Facility Location: 1801 Brown Avenue
Norfolk, Virginia 23504

Registration Number: 61274
Permit Number: TRO-61274

This permit includes the following programs:

Federally Enforceable Requirements - Clean Air Act (Sections I through X)

State Only Enforceable Requirements (Section XI)

September 10, 2012

Effective Date

September 9, 2017

Expiration Date

Maria R. Nold

September 10, 2012

Signature Date

Table of Contents, 2 pages
Permit Conditions, 27 pages

Table of Contents

I. FACILITY INFORMATION.....4

II. EMISSION UNITS.....6

III. FUEL BURNING EQUIPMENT REQUIREMENTS – (EMISSION UNIT ID#16, 17, EG-1, AND FP-1)7

A. LIMITATIONS7

B. MONITORING.....7

C. RECORDKEEPING.....7

D. TESTING8

IV. ABRASIVE BLASTING REQUIREMENTS – (REF. NOS. 7-15).....9

A. LIMITATIONS9

B. RECORDKEEPING.....10

C. TESTING10

V. COATING AND CLEANING OPERATION REQUIREMENTS – (REF. NOS. 1-6).....10

A. LIMITATIONS10

B. RECORDKEEPING.....12

C. TESTING12

VI. DEGREASING OPERATIONS - NON-HALOGENATED COLD DEGREASER (REF. NO. DC)13

A. LIMITATIONS13

B. MONITORING.....13

C. RECORDKEEPING.....14

VII. MACT, SUBPART II SHIPBUILDING AND REPAIR REQUIREMENTS.....15

A. LIMITATIONS15

B. COMPLIANCE PROCEDURES.....15

C. MONITORING, RECORDKEEPING, AND REPORTING16

VIII. INSIGNIFICANT EMISSION UNITS18

IX. PERMIT SHIELD & INAPPLICABLE REQUIREMENTS18

X. GENERAL CONDITIONS19

A. FEDERAL ENFORCEABILITY19

B. PERMIT EXPIRATION.....19

C. RECORDKEEPING AND REPORTING19

D. ANNUAL COMPLIANCE CERTIFICATION.....20

E. PERMIT DEVIATION REPORTING21

F. FAILURE/MALFUNCTION REPORTING21

G. SEVERABILITY21

H. DUTY TO COMPLY21

I. NEED TO HALT OR REDUCE ACTIVITY NOT A DEFENSE.....22

J. PERMIT MODIFICATION22

K. PROPERTY RIGHTS22

L. DUTY TO SUBMIT INFORMATION22

M. DUTY TO PAY PERMIT FEES22

N. FUGITIVE DUST EMISSION STANDARDS.....22

O. STARTUP, SHUTDOWN, AND MALFUNCTION.....23

P. ALTERNATIVE OPERATING SCENARIOS23

Q. INSPECTION AND ENTRY REQUIREMENTS.....23

R. REOPENING FOR CAUSE24

S. PERMIT AVAILABILITY24

T. TRANSFER OF PERMITS.....24

U.	MALFUNCTION AS AN AFFIRMATIVE DEFENSE.....	24
V.	PERMIT REVOCATION OR TERMINATION FOR CAUSE.....	25
W.	DUTY TO SUPPLEMENT OR CORRECT APPLICATION	25
X.	STRATOSPHERIC OZONE PROTECTION	25
Y.	ASBESTOS REQUIREMENTS.....	25
Z.	ACCIDENTAL RELEASE PREVENTION.....	26
AA.	CHANGES TO PERMITS FOR EMISSIONS TRADING	26
BB.	EMISSIONS TRADING	26
XI.	STATE-ONLY ENFORCEABLE REQUIREMENTS.....	27

I. Facility Information

Permittee
Lyon Shipyard, Inc.
PO Box 2180
Norfolk, Virginia 23501

Responsible Official
Thomas Ackiss
Vice President

Facility
Lyon Shipyard, Inc.
1801 Brown Avenue
Norfolk, Virginia 23504

Contact Person
Thomas Beacham
Environmental Manager
(757) 622-4661

County-Plant Identification Number: 51-710-00249

Facility Description:

NAICS 336611 -- Ship Building and Repairing

Lyon Shipyard, Inc. functions primarily as a ship repair facility.

Abrasive Grit Blasting: To prepare the ship for painting, power washing is performed using portable power washers and/or abrasive blasting is performed using grit blasting material. The blasting is performed by nine abrasive blast units permitted in the July 10, 2010 State Operating Permit.

The abrasive blasting is performed by using the abrasive grit blasting units. Grit is supplied to the units using portable abrasive grit pots. These pots are filled with grit (1) pneumatically from a delivery tanker truck, (2) from two on-site grit storage silos (25 ton capacity per silo) or (3) manually pouring the grit into the pot. The particulate emissions from filling the abrasive grit pots are controlled by venting the exhaust from the pot through a 55 gallon drum of water. The particulate emissions from filling the silos are controlled by venting the silo exhaust through a 55 gallon drum of water; or for the storage silo located adjacent to the Blast Building, the silo is vented to the Blast Building. The Blast Building is enclosed and is not vented to the ambient air.

Blasting Process – Metal Building: Metal parts are prepared for painting inside the Blast Building using abrasive grit. The grit is pneumatically supplied by a abrasive grit pot located under the abrasive grit silo located adjacent to the building. The Blast Building is enclosed. The abrasive grit is the same as used in the Abrasive Blasting and is included in the reporting of the permitted abrasive blasting material usage required by the July 10, 2010 State Operating Permit

Blasting Process – Miscellaneous: Smaller metal parts are blasted for cleaning and/or preparation for painting inside the Wheelabrator Building. The blasting occurs in an enclosed, nonvented hand cabinet or in a Pangborne ES-1885-32 Rotobast machine. The Pangborn unit is equipped with a dust collector that is vented to the ambient air. The blast material used is steel shot. Nonvented hand cabinet blast units may be used in other parts of the facility.

Painting: Painting performed on ships in both wet and dry docks is addressed by the six airless pump spray guns in the July 10, 2010 State Operating Permit. Individual metal parts are also painted in several areas in the facility, including the Wheelabrator Building. The paint applied at these locations is included in the reporting of the permitted usage of the paint required by the July 10, 2010 State Operating Permit. The facility is subject to the Shipyard MACT, Subpart II.

Metal Shop Fabrication and Machine Shops: Metal fabrication is performed at several locations at the facility, including a metal shop fabrication that has a plasma torch unit that cuts pieces of metal. This unit is vented to the ambient air.

Burning (cutting) and welding are performed at different locations, including inside buildings and outside.

Wood Working: Lyon Shipyard, Inc. has a wood working operation consisting of several pieces of wood working equipment. Sawdust generated from this equipment is collected by a pneumatic system and transferred to a bin that is located inside the building. The pneumatic system is equipped with a cyclone.

Hand applied stain and sealer may be used on some wood pieces for repairing of ships.

Fuel Burning: Fuel burning equipment includes two distillate oil-fired boilers, each rated at 3.45 MMBtu/hr each. These boilers provide hot water for ships that are being repaired. Several distillate oil-fired space heaters provide space heating to buildings. Two space heaters rated at 0.28 MMBtu/hr and 0.35 MMBtu/hr also burn on-site generated used oil.

Lyon Shipyard, Inc. has two emergency stationary engines that burn No. 2 Fuel Oil and are used as follows:

- 500 kW (670 HP) rated capacity No. 2 Fuel Oil-fired stationary emergency generator used to provide emergency power for the floating dry dock: MACT, Subpart ZZZZ applies. However, the only applicable requirement is the initial notification.
- 200 HP rated capacity No. 2 Fuel Oil-fired stationary pump for fire suppression: MACT, Subpart ZZZZ applies. Because of the August 20, 2010 amendment to Subpart ZZZZ, the compliance date for the applicable requirements of Subpart ZZZZ is May 3, 2013.

Lyon Shipyard, Inc. has several portable engines that provide electrical or mechanical power for operating power waters, pumps, etc.

Miscellaneous: Cleaning of metal parts may be performed by use of non-halogenated solvents. There are two other miscellaneous operations or emission units that are insignificant from a Title V perspective. These operations include facility maintenance, storage tanks for No. 2 Fuel Oil, used oil, oil/water from compressor blowdown, and use of fuel oil for space heating. The emergency generator and water fire pump are insignificant based on emissions. However, the engines are subject to MACT, Subpart ZZZZ and therefore cannot be considered insignificant for the purposes of Title V permitting.

The facility is a Title V major source of HAP. This source is located in an attainment area for all pollutants, and is a PSD minor source.

II. Emission Units

Equipment to be operated consists of:

Emission Unit ID	Stack ID	Emission Unit Description	Size/Rated Capacity*	Pollution Control Device (PCD) Description	PCD ID	Pollutant Controlled	Applicable Permit Date
Fuel Burning Equipment							
16	BS-1	Cyclotherm Model MC-1500 distillate oil-fired boiler	3.45 MMBtu/hr	None	-	-	July 20, 2010
17	BS-2	Cyclotherm Model MC-1500 distillate oil-fired boiler	3.45 MMBtu/hr	None	-	-	July 20, 2010
EG-1	EGS-1	Diesel fired Emergency Generator	500 kW	None	-	-	July 20, 2010
FP-1	FPS-1	Diesel fired fire pump	200 hp	None	-	-	July 20, 2010
Abrasive Blasting							
7 – 15	NA	Nine (9) - Abrasive grit blasting units (nozzles as sources)	6 tons/hr (total)	None	-	-	July 20, 2010
Spray Painting							
1 – 6	NA	Six (6) - Airless pumps with spray gun applicators (nozzles as sources)	540 gal/hr (total)	None	-	-	July 20, 2010
Degreasing Operations - Non-Halogenated Cold Degreaser							
DC	NA	Cold Solvent Degreaser sinks	-	None	-	-	-

*The Size/Rated capacity [and PCD efficiency] is provided for informational purposes only, and is not an applicable requirement.

III. Fuel Burning Equipment Requirements – (emission unit ID#16, 17, EG-1, and FP-1)

A. Limitations

1. Visible Emissions from each of the two (2) boiler stacks (Ref. Nos. BS-1 and BS-2) shall not exceed twenty (20) percent opacity except during one six-minute period in any one hour in which visible emissions shall not exceed thirty (30) percent opacity.
(9 VAC 5-50-80 and 9 VAC 5-80-110)
2. Except where this permit is more restrictive than the applicable requirement, the boilers (Ref. Nos. 16 and 17) shall be operated in compliance with the requirements of 40 CFR 63, Subpart DDDDD when it becomes final.
(9 VAC 5-80-110)
3. Boiler emissions shall be controlled by proper operation and maintenance. Boiler operators shall be trained in the proper operation of all such equipment. Training shall consist of a review and familiarization of the manufacturer's operating instructions, at minimum.
(9 VAC 5-80-110)
4. The existing emergency CI generator and emergency fire pump (Ref. Nos. EG-1 and FP-1) shall be in compliance with 40 CFR Part 63, Subpart ZZZZ by May 3, 2013. These units shall comply with 40 CFR 63.6640(f).
(9 VAC 5-80-110 and 40 CFR 63, Subpart ZZZZ)

B. Monitoring

1. The permittee shall perform a monthly visual emissions observation on each boiler stack (Ref. Nos. 16 and 17) during normal operations. If such visual observation indicates any visible emissions, the permittee shall take corrective actions to eliminate the visible emissions. If such corrective action fails to eliminate visible emissions, the permittee shall conduct a visible emissions evaluation (VEE) using 40 CFR Part 60, Appendix A, Method 9 for six minutes. If the six-minute VEE opacity average exceeds 50% of the standard for a specific unit, the VEE for that unit shall continue for an additional 12 minutes. If any of the six-minute averages during the 18 minutes exceeds the standard for a specific unit, the VEE for that unit shall continue for one hour from initiation on the stack to determine compliance with the opacity limit. The permittee shall record the details of the visual emissions observations, VEE, and any corrective actions. The records shall be kept at the facility and made available for inspection by the DEQ for the most recent five (5) year period.
(9 VAC 5-80-110)

C. Recordkeeping

1. The permittee shall maintain records of all emission data and operating parameters necessary to demonstrate compliance with this permit. The content and format of such records shall be arranged with the Director, Tidewater Regional Office. These records shall include, but are not limited to:

- a) Monthly visual opacity observations log.
- b) Records as necessary to demonstrate compliance with 40 CFR 63 Subpart ZZZZ for the engines and generators (Ref. Nos. EG-1 and FP-1).

These records shall be available on site for inspection by the DEQ and shall be current for the most recent (5) years.

(9 VAC 5-50-50 and 9 VAC 5-80-110)

D. Testing

- 1. If testing is conducted in addition to the monitoring specified in this permit, the permittee shall use the appropriate method(s) in accordance with procedures approved by the DEQ.
(9 VAC 5-80-110)

IV. Abrasive Blasting Requirements – (Ref. Nos. 7-15)

A. Limitations

1. The throughput of abrasive blast material shall not exceed 24,500 tons per year, calculated monthly as the sum of each consecutive 12-month period. Compliance for the consecutive 12-month period shall be demonstrated monthly by adding the total for the most recently completed calendar month to the individual monthly totals for the preceding 11 months.
(9 VAC 5-80-110 and Condition 4 of 5/10/12 SOP Permit)

2. Particulate emissions from the abrasive blasting operations at the ship repair facility shall not exceed the limits specified below:

PM	245.0 tons/yr
PM-10	122.5 tons/yr

These emissions are derived from the estimated overall emission contribution from operating limits. Exceedance of the operating limits may be considered credible evidence of the exceedance of emission limits. Compliance with these emission limits may be determined as stated in Condition IV.A.1 and IV.B.1 of this permit.
(9 VAC 5-80-110, 9 VAC 5-50-260 and Condition 9 of 5/10/12 SOP Permit)

3. **Shipyard Memorandum of Understanding (MOU)** - The permittee shall provide/perform the following:
 - a) Establish, implement, and submit a written policy and procedure for outdoor abrasive blasting operations which takes “reasonable precautions to prevent particulate matter from becoming airborne.”
 - b) Install wind direction and wind speed instruments located conveniently to central shipyard outdoor abrasive blasting operations, and shall maintain records of wind direction and speed.
 - c) Minimize, or if necessary terminate, outdoor abrasive blasting operations if the prevailing wind direction and speed cause particulate matter from such activities to be transported to adjacent property.
 - d) Terminate abrasive blasting operations if the wind speed exceeds a sustained 25 miles per hour at the facility, unless effective containment methods are utilized or wind direction is such that particulate matter will not be improperly transported to adjacent property.
 - e) Use adequate containment methods such as curtains and shrouds where possible and practical, and locate the operations to minimize particulate matter from being transported to adjacent property.
 - f) Use airless spray equipment and spray in a horizontal to down pattern to the maximum extent possible and practicable.
 - g) Endeavor to conduct abrasive blasting operations in a manner consistent with the Federal Clean Air Act, Virginia Air Pollution Control Law, and regulations promulgated there under, as applicable.

(9 VAC 5-80-110, NORSHIPCO letter dated February 12, 1990, and Condition 13 of 5/10/12 SOP Permit)

B. Recordkeeping

1. The permittee shall maintain records of all emission data and operating parameters necessary to demonstrate compliance with this permit and the Shipyard MOU. The content and format of such records shall be arranged with the Director, Tidewater Regional Office. These records shall include, but are not limited to:
 - a) Annual throughput of abrasive blast material, calculated monthly as the sum of each consecutive 12-month period. Compliance for the consecutive 12-month period shall be demonstrated monthly by adding the total for the most recently completed calendar month to the individual monthly totals for the preceding 11 months;
 - b) Records of wind direction and speed for the outdoor abrasive blasting, as required by Condition IV.A.3.b); and
 - c) Records as required by the MACT Subpart II.

These records shall be available on site for inspection by the DEQ and shall be current for the most recent five (5) years.

(9 VAC 5-50-50, 9 VAC 5-80-110 and Condition 14 of 5/10/12 SOP Permit)

C. Testing

1. If testing is conducted in addition to the monitoring specified in this permit, the permittee shall use the appropriate method(s) in accordance with procedures approved by the DEQ.
(9 VAC 5-80-110)

V. Coating and Cleaning Operation Requirements – (Ref. Nos. 1-6)

A. Limitations

1. The throughput of coating media, as applied to marine vessels and marine parts, shall not exceed 126,212 gallons per year, calculated monthly as the sum of each consecutive 12-month period. Compliance for the consecutive 12-month period shall be demonstrated monthly by adding the total for the most recently completed calendar month to the individual monthly totals for the preceding 11 months.
(9 VAC 5-80-110 and Condition 5 of 5/10/12 SOP Permit)
2. The throughput of solvents used to clean the spray applicator guns and associated equipment shall not exceed 9,187.5 gallons per year, calculated monthly as the sum of each consecutive 12-month period. Compliance for the consecutive 12-month period shall be demonstrated monthly by adding the total for the most recently completed calendar month to the individual monthly totals for the preceding 11 months.
(9 VAC 5-80-110 and Condition 6 of 5/10/12 SOP Permit)
3. The VOC content in any of the solvents used to clean the spray applicator guns and associated equipment shall not exceed 8.0 pounds VOC per gallon of product (lbs/gal), less water and exempt compounds. An exempt compound refers to a compound that has been excluded from the official definition of volatile organic compounds as found in 9 VAC 5-10-20 of the Regulations.
(9 VAC 5-80-110 and Condition 7 of 5/10/12 SOP Permit)

4. At all times the disposal of volatile organic compounds shall be accomplished by taking measures, to the extent practicable, consistent with air pollution control practices for minimizing emissions. Volatile organic compounds shall not be intentionally spilled, discarded in sewers which are not connected to a treatment plant, or stored in open containers, or handled in any other manner that would result in evaporation beyond that consistent with air pollution practices for minimizing emissions.
(9 VAC 5-80-110 and Condition 3 of 5/10/12 SOP Permit)
5. VOC emissions from spray coating applications, combined, shall not exceed the limits specified below:

Volatile Organic Compounds	208.3 tons/yr
----------------------------	---------------

These emissions are derived from the estimated overall emission contribution from operating limits. Exceedance of the operating limits may be considered credible evidence of the exceedance of emission limits. Compliance with these emission limits may be determined as stated in Conditions V.A.1, and V.B.1 of this permit.
(9 VAC 5-80-110 and Condition 10 of 5/10/12 SOP Permit)
6. VOC emissions from operations involving the cleaning and/or purging of spray applicator equipment, combined, shall not exceed the limits specified below:

Volatile Organic Compounds	1.8 tons/yr
----------------------------	-------------

These emissions are derived from the estimated overall emission contribution from operating limits. Exceedance of the operating limits may be considered credible evidence of the exceedance of emission limits. Compliance with these emission limits may be determined as stated in Conditions V.A.2, V.A.3 and V.B.1 of this permit.
(9 VAC 5-80-110 and Condition 11 of 5/10/12 SOP Permit)
7. **Shipyard Memorandum of Understanding (MOU)** - The permittee shall provide/perform the following:
 - a) Establish, implement, and submit a written policy and procedure for outdoor spray painting operations which takes "reasonable precautions to prevent particulate matter from becoming air borne."
 - b) Install wind direction and wind speed instruments located conveniently to central shipyard outdoor spray painting operations, and shall maintain records of wind direction and speed.
 - c) Minimize, or if necessary terminate, outdoor spray painting operations if the prevailing wind direction and speed cause particulate matter from such activities to be transported to adjacent property.
 - d) Terminate spray painting operations if the wind speed exceeds a sustained 25 miles per hour at the facility, unless effective containment methods are utilized or wind direction is such that particulate matter will not be improperly transported to adjacent property.
 - e) Use adequate containment methods such as curtains and shrouds where possible and practical, and locate the operations to minimize particulate matter from being transported to adjacent property.
 - f) Use airless spray equipment and spray in a horizontal to down pattern to the maximum extent possible and practicable.

- g) Endeavor to conduct spray painting operations in a manner consistent with the Federal Clean Air Act, Virginia Air Pollution Control Law, and regulations promulgated there under, as applicable.

(9 VAC 5-80-110, NORSHIPCO letter dated February 12, 1990, and Condition 13 of 5/10/12 SOP Permit)

B. Recordkeeping

1. The permittee shall maintain records of all emission data and operating parameters necessary to demonstrate compliance with this permit. The content and format of such records shall be arranged with the Director, Tidewater Regional Office. These records shall include, but are not limited to:
 - a) Annual throughput of coating media in gallons, as applied to marine vessels and marine parts, calculated monthly as the sum of each consecutive 12-month period. Compliance for the consecutive 12-month period shall be demonstrated monthly by adding the total for the most recently completed calendar month to the individual monthly totals for the preceding 11 months;
 - b) Annual throughput of solvents/thinners used to clean the spray guns and associated equipment in gallons, calculated monthly as the sum of each consecutive 12-month period. Compliance for the consecutive 12-month period shall be demonstrated monthly by adding the total for the most recently completed calendar month to the individual monthly totals for the preceding 11 months;
 - c) Material Safety Data Sheets (MSDS) or other vendor information as approved by DEQ showing the VOC and HAP contents for each coating media and solvent/thinner used;
 - d) Records as required by the MACT Subpart II.
 - e) Records of wind direction and speed for the outdoor abrasive blasting and spray painting operations, as required by Condition V.A.7.b).

These records shall be available on site for inspection by the DEQ and shall be current for the most recent five (5) years.

(9 VAC 5-50-50, 9 VAC 5-80-110 and Condition 14 of 5/10/12 SOP Permit)

C. Testing

1. If testing is conducted in addition to the monitoring specified in this permit, the permittee shall use the appropriate method(s) in accordance with procedures approved by the DEQ.
(9 VAC 5-80-110)

VI. Degreasing Operations - Non-Halogenated Cold Degreaser (Ref. No. DC)

A. Limitations

1. Vapor control is required for the cold cleaner (Ref. No. DC) to remove, destroy, or prevent the discharge into the atmosphere of at least 85% by weight of volatile organic compound emissions. Achievement of the 85% vapor control shall be done by the following:
 - a) Covers or enclosed remote reservoirs;
 - b) Drainage facilities to collect and return solvent to a closed container or a solvent cleaning machine;
 - c) A permanent label, summarizing the operating procedures in 9 VAC 5-40-3290 C.2.a-c on/near the cold cleaning unit(s);
 - d) If used, the solvent spray should be a solid, fluid stream (not a fine, atomized or shower type spray) and at a pressure which does not cause excessive splashing.(9 VAC 5-80-110, 9 VAC 5-40-3280 C.1 & 2, and 9 VAC 5-40-3290.C.1.a-d)
2. The following operating procedures for the cold cleaning units (Ref. No. DC) shall be followed:
 - a) Waste solvent should not be disposed of or transferred to another party, such that greater than 20% of the waste (by weight) can evaporate to the atmosphere. Waste solvent shall be stored in closed containers only.
 - b) The cold cleaning unit cover should be closed whenever not handling parts in the cold cleaner.
 - c) Cleaned parts should drain for at least 15 seconds or until dripping ceases.(9 VAC 5-80-110, 9 VAC 5-40-3280 C.1 & 2, and 9 VAC 5-40-3290.C.2.a-c)
3. Disposal of waste solvent from the cold cleaning units (Ref. No. DC) shall be done by one of the following:
 - a) Reclamation (either by outside services or in-house), or
 - b) Incineration by approved company.(9 VAC 5-80-110, 9 VAC 5-40-3280 C.1 & 2, and 9 VAC 5-40-3290.D)

B. Monitoring

1. The degreasing unit (Ref. No. DC) will be inspected once per calendar year to ensure that the label with the operating procedures is placed on or near each degreasing unit.
 2. The degreasing unit (Ref. No. DC) will be inspected once per calendar year to ensure that each has a cover or enclosed remote reservoir, and waste solvent from each unit is stored in closed containers.
- (9 VAC 5-80-110 E)

C. Recordkeeping

The permittee shall maintain records of all emission data and operating parameters necessary to demonstrate compliance with this permit. The content and format of such records shall be arranged with the Director, Tidewater Regional Office. These records shall include, but are not limited to:

1. Annual inspection results and any corrective actions taken;
2. Method(s) of waste solvent disposal.

These records shall be available on site for inspection by the DEQ and shall be current for the most recent five (5) years.

(9 VAC 5-80-110)

VII. MACT, Subpart II Shipbuilding and Repair Requirements

A. Limitations

1. Each owner or operator shall ensure that:
 - a) All handling and transfer of VOHAP-containing materials to and from containers, tanks, vats, drums, and piping systems is conducted in a manner that minimizes spills.
 - b) All containers, tanks, vats, drums, and piping systems are free of cracks, holes, and other defects and remain closed unless materials are being added to or removed from them.

(9 VAC 5-60-100, 9 VAC 5-80-110, and 40 CFR 63.783(b))
2. The shipbuilding and ship repair operation is to be operated in compliance with the requirements of 40 CFR 63 Subpart II (Shipbuilding and Ship Repair (Surface Coating)) and the general provisions of 40 CFR 63 Subpart A, as specified in Table 1 of 40 CFR 63 Subpart II.
(9 VAC 5-60-100, 9 VAC 5-80-110, and 40 CFR 63.780)
3. The provisions of 40 CFR Part 63, Subpart II do not apply to “low-usage exempt” coatings used in volumes of less than 52.8 gallons per year for each coating, and 264 gallons per year of all such coatings. Coatings exempt under this condition shall be clearly labeled as “low-usage exempt”.
(9 VAC 5-60-100, 9 VAC 5-80-110, and 40 CFR 63.781(b))
4. The provisions of 40 CFR Part 63 Subpart A pertaining to startups, shutdowns, and malfunctions and continuous monitoring do not apply unless an add-on control system is used to comply with 40 CFR Part 63 Subpart II.
(9 VAC 5-60-100, 9 VAC 5-80-110, and 40 CFR 63.781(d))
5. No owner or operator shall cause or allow the application of any coating to a ship with an as-applied Volatile Organic Hazardous Air Pollutant (VOHAP) content exceeding the applicable limit given in Table 2 of 40 CFR part 63 Subpart II.
(9 VAC 5-60-100, 9 VAC 5-80-110, and 40 CFR 63.783(a))

B. Compliance Procedures

1. For each batch of coating that is received, the owner or operator shall:
 - a) Determine the coating category and the applicable VOHAP limit as specified in 40 CFR 63.783(a).
 - b) Certify the as-supplied VOC content of the batch of coating.

(9 VAC 5-60-100, 9 VAC 5-80-110, and 40 CFR 63.785(a))
2. In lieu of testing each batch of coating, as applied, the owner or operator may determine compliance with the VOHAP limits using any combination of the procedures described in 40 CFR 63.785 (c)(1), (c)(2), (c)(3), and (c)(4). The procedure used for each coating shall be determined and documented prior to application.
(9 VAC 5-60-100, 9 VAC 5-80-110, and 40 CFR 63.785(b)(1))
3. The results of any compliance demonstration using Method 24 shall take precedence over the results using the procedures in 40 CFR 63.785 (c)(1), (c)(2), or (c)(3).
(9 VAC 5-60-100, 9 VAC 5-80-110, and 40 CFR 63.785(b)(2))

4. The results of any compliance demonstration conducted using an approved test method to determine VOHAP content shall take precedence over the results using the procedures in 40 CFR 63.785(c)(4). (9 VAC 5-60-100, 9 VAC 5-80-110, and 40 CFR 63.785(b)(3))

C. Monitoring, Recordkeeping, and Reporting

1. For each compliance procedure used (40 CFR 63.785(c)(1), (2), (3), and (4)), the permittee shall maintain records to demonstrate compliance with the chosen procedure. (9 VAC 5-80-110 and 40 CFR 63.788(b)(2) and (3))
2. Each owner or operator shall comply with the applicable recordkeeping and reporting requirements in 40 CFR 63.10(a), (b), (d), and (f). (9 VAC 5-60-100, 9 VAC 5-80-110, and 40 CFR 63.788(a))
3. Each owner or operator of a major source shipbuilding or ship repair facility having surface coating operations with less than 264 gallons annual marine coating usage shall record the total volume of coating applied at the source to ships. Such records shall be compiled monthly and maintained for a minimum of 5 years. (9 VAC 5-60-100, 9 VAC 5-80-110, and 40 CFR 63.788(b)(1))
4. Each owner or operator of an affected source shall compile records on a monthly basis and maintain those records for a minimum of 5 years. At a minimum, these records shall include:
 - a) All documentation supporting initial notification;
 - b) A copy of the affected source's implementation plan;
 - c) The volume of each low-usage-exempt coating applied;
 - d) Identification of the coating used, their appropriate coating categories, and the applicable VOHAP limit;
 - e) Certification of the as-supplied VOC content of each batch of coating;
 - f) A determination of whether containers meet the standards as described in 40 CFR 63.783(b)(2); and
 - g) The results of any Method 24 of Appendix A or 40 CFR Part 60 or approved VOHAP measurement test conducted on individual containers of coating, as applied.
 - h) Any additional information, as determined by the compliance procedure(s) described in 40 CFR 63.785(c) that the permittee followed.(9 VAC 5-60-100, 9 VAC 5-80-110, 40 CFR 63.788 (b)(2), and 40 CFR 63.788(b)(3))
5. If the owner or operator detects a violation of the standard specified in 40 CFR 63.783, the owner or operator shall, for the remainder of the reporting period during which the violation(s) occurred, include the information listed in 40 CFR 63.788 (b)(4) in the facility records. (9 VAC 5-60-100, 9 VAC 5-80-110, and 40 CFR 63.788 (b)(4))

6. Before the 60th day following completion of each 6-month period after the compliance date specified in 40 CFR 63.784, each owner or operator of an affected source shall submit a report to the EPA Administrator and the DEQ Tidewater Regional Office for each of the previous 6 months. The report shall include all of the information that must be retained pursuant to paragraphs (b)(2) through (3) of 40 CFR 63.788, except for that specified in paragraphs (b)(2)(i) through (ii), (b)(2)(v), (b)(3)(i)(A), (b)(3)(ii)(A), and (b)(3)(iii)(A). If a violation is detected, the source shall also report the information specified in paragraph (b)(4) of 40 CFR 63.788 for the reporting period during which the violation(s) occurred. To the extent possible, the report shall be organized according to the compliance procedure(s) followed each month by the affected source.

One copy of the above referenced report shall be sent to the EPA Administrator at the following address:

Associate Director
Office of Air Enforcement and Compliance Assistance (3AP20)
U.S. Environmental Protection Agency
Region III
1650 Arch Street
Philadelphia, PA 19103-2029

(9 VAC 5-60-100, 9 VAC 5-80-110, and 40 CFR 63.788 (c))

VIII. Insignificant Emission Units

The following emission units at the facility are identified in the application as insignificant emission units under 9 VAC 5-80-720:

Emission Unit No.	Emission Unit Description	Citation	Pollutant(s) Emitted (9 VAC 5-80-720 B)	Rated Capacity (9 VAC 5-80-720 C)
BO-3	Pangborne ES-1885-32 Roboblast	9 VAC 5-80-720.B.1	PM	5 tons/yr
WW	Wood Working Shop	9 VAC 5-80-720.B.1	PM	3 tons/yr
MF	Metal Fabrication	9 VAC 5-80-720.B.1	PM	
PW	Portable Gasoline/Diesel Fired Power Washer	9 VAC 5-80-720.B.1	PM, SO ₂ , CO, NO _x	

These emission units are presumed to be in compliance with all requirements of the federal Clean Air Act as may apply. Based on this presumption, no monitoring, recordkeeping, or reporting shall be required for these emission units in accordance with 9 VAC 5-80-110.

IX. Permit Shield & Inapplicable Requirements

Compliance with the provisions of this permit shall be deemed compliance with all applicable requirements in effect as of the permit issuance date as identified in this permit. This permit shield covers only those applicable requirements covered by terms and conditions in this permit and the following requirements which have been specifically identified as being not applicable to this permitted facility:

Citation	Title of Citation	Description of Applicability

Nothing in this permit shield shall alter the provisions of §303 of the federal Clean Air Act, including the authority of the administrator under that section, the liability of the owner for any violation of applicable requirements prior to or at the time of permit issuance, or the ability to obtain information by the administrator pursuant to §114 of the federal Clean Air Act, (ii) the Board pursuant to §10.1-1314 or §10.1-1315 of the Virginia Air Pollution Control Law or (iii) the Department pursuant to §10.1-1307.3 of the Virginia Air Pollution Control Law.
 (9 VAC 5-80-140)

X. General Conditions

A. Federal Enforceability

All terms and conditions in this permit are enforceable by the administrator and citizens under the federal Clean Air Act, except those that have been designated as only state-enforceable.

(9 VAC 5-80-110 N)

B. Permit Expiration

This permit has a fixed term of five years. The expiration date shall be the date five years from the date of issuance. Unless the owner submits a timely and complete application for renewal to the Department consistent with the requirements of 9 VAC 5-80-80, the right of the facility to operate shall be terminated upon permit expiration.

1. The owner shall submit an application for renewal at least six months but no earlier than eighteen months prior to the date of permit expiration.
2. If an applicant submits a timely and complete application for an initial permit or renewal under this section, the failure of the source to have a permit or the operation of the source without a permit shall not be a violation of Article 1, Part II of 9 VAC 5 Chapter 80, until the Board takes final action on the application under 9 VAC 5-80-150.
3. No source shall operate after the time that it is required to submit a timely and complete application under subsections C and D of 9 VAC 5-80-80 for a renewal permit, except in compliance with a permit issued under Article 1, Part II of 9 VAC 5 Chapter 80.
4. If an applicant submits a timely and complete application under section 9 VAC 5-80-80 for a permit renewal but the Board fails to issue or deny the renewal permit before the end of the term of the previous permit, (i) the previous permit shall not expire until the renewal permit has been issued or denied and (ii) all the terms and conditions of the previous permit, including any permit shield granted pursuant to 9 VAC 5-80-140, shall remain in effect from the date the application is determined to be complete until the renewal permit is issued or denied.
5. The protection under subsections F 1 and F 5 (ii) of section 9 VAC 5-80-80 F shall cease to apply if, subsequent to the completeness determination made pursuant section 9 VAC 5-80-80 D, the applicant fails to submit by the deadline specified in writing by the Board any additional information identified as being needed to process the application.

(9 VAC 5-80-80 B, C, and F, 9 VAC 5-80-110 D and 9 VAC 5-80-170 B)

C. Recordkeeping and Reporting

1. All records of monitoring information maintained to demonstrate compliance with the terms and conditions of this permit shall contain, where applicable, the following:
 - a) The date, place as defined in the permit, and time of sampling or measurements.
 - b) The date(s) analyses were performed.
 - c) The company or entity that performed the analyses.
 - d) The analytical techniques or methods used.
 - e) The results of such analyses.

f) The operating conditions existing at the time of sampling or measurement.

(9 VAC 5-80-110 F)

2. Records of all monitoring data and support information shall be retained for at least five years from the date of the monitoring sample, measurement, report, or application. Support information includes all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by the permit.

(9 VAC 5-80-110 F)

3. The permittee shall submit the results of monitoring contained in any applicable requirement to DEQ no later than **March 1st** and **September 1st** of each calendar year. This report must be signed by a responsible official, consistent with 9 VAC 5-80-80 G, and shall include:

a) The time period included in the report. The time periods to be addressed are January 1st to June 30th and July 1st to December 31st.

b) All deviations from permit requirements. For purpose of this permit, deviations include, but are not limited to:

(1) Exceedance of emissions limitations or operational restrictions;

(2) Excursions from control device operating parameter requirements, as documented by continuous emission monitoring, periodic monitoring, or Compliance Assurance Monitoring (CAM) which indicates an exceedance of emission limitations or operational restrictions; or,

(3) Failure to meet monitoring, recordkeeping, or reporting requirements contained in this permit.

c) If there were no deviations from permit conditions during the time period, the permittee shall include a statement in the report that "no deviations from permit requirements occurred during this semi-annual reporting period."

(9 VAC 5-80-110 F)

D. Annual Compliance Certification

Exclusive of any reporting required to assure compliance with the terms and conditions of this permit or as part of a schedule of compliance contained in this permit, the permittee shall submit to EPA and DEQ no later than March 1 each calendar year a certification of compliance with all terms and conditions of this permit including emission limitation standards or work practices for the period ending December 31. The compliance certification shall comply with such additional requirements that may be specified pursuant to §114(a)(3) and §504(b) of the federal Clean Air Act. The permittee shall maintain a copy of the certification for five (5) years after submittal of the certification. This certification shall be signed by a responsible official, consistent with 9 VAC 5-80-80 G, and shall include:

1. The time period included in the certification. The time period to be addressed is January 1st to December 31st.

2. The identification of each term or condition of the permit that is the basis of the certification.

3. The compliance status.

4. Whether compliance was continuous or intermittent, and if not continuous, documentation of each incident of non-compliance.

5. Consistent with subsection 9 VAC 5-80-110 E, the method or methods used for determining the compliance status of the source at the time of certification and over the reporting period.
6. Such other facts as the permit may require to determine the compliance status of the source.
7. One copy of the annual compliance certification shall be submitted to EPA in electronic format only. The certification document should be sent to the following electronic mailing address:

R3_APD_Permits@epa.gov

(9 VAC 5-80-110 K.5)

E. Permit Deviation Reporting

The permittee shall notify the Director, Tidewater Regional Office within four daytime business hours after discovery of any deviations from permit requirements which may cause excess emissions for more than one hour, including those attributable to upset conditions as may be defined in this permit. In addition, within 14 days of the discovery, the permittee shall provide a written statement explaining the problem, any corrective actions or preventative measures taken, and the estimated duration of the permit deviation. [Owners subject to the requirements of 9 VAC 5-40-50 C and 9 VAC 5-50-50 C are not required to provide the written statement prescribed in this paragraph for facilities subject to the monitoring requirements of 9 VAC 5-40-40 and 9 VAC 5-50-40.] The occurrence should also be reported in the next semi-annual compliance monitoring report pursuant to General Condition IX.C.3 of this permit.

(9 VAC 5-80-110 F.2 and 9 VAC 5-80-250)

F. Failure/Malfunction Reporting

In the event that any affected facility or related air pollution control equipment fails or malfunctions in such a manner that may cause excess emissions for more than one hour, the owner shall, as soon as practicable but no later than four daytime business hours after the malfunction is discovered, notify the Director, Tidewater Regional Office by facsimile transmission, telephone or telegraph of such failure or malfunction and shall within 14 days of discovery provide a written statement giving all pertinent facts, including the estimated duration of the breakdown. Owners subject to the requirements of 9 VAC 5-40-50 C and 9 VAC 5-50-50 C are not required to provide the written statement prescribed in this paragraph for facilities subject to the monitoring requirements of 9 VAC 5-40-40 and 9 VAC 5-50-40. When the condition causing the failure or malfunction has been corrected and the equipment is again in operation, the owner shall notify the Director, Tidewater Regional Office.

(9 VAC 5-20-180 C)

G. Severability

The terms of this permit are severable. If any condition, requirement or portion of the permit is held invalid or inapplicable under any circumstance, such invalidity or inapplicability shall not affect or impair the remaining conditions, requirements, or portions of the permit.

(9 VAC 5-80-110 G.1)

H. Duty to Comply

The permittee shall comply with all terms and conditions of this permit. Any permit noncompliance constitutes a violation of the federal Clean Air Act or the Virginia Air Pollution Control Law or both and is ground for enforcement action; for permit termination, revocation and reissuance, or modification; or, for denial of a permit renewal application.

(9 VAC 5-80-110 G.2)

I. Need to Halt or Reduce Activity not a Defense

It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

(9 VAC 5-80-110 G.3)

J. Permit Modification

A physical change in, or change in the method of operation of, this stationary source may be subject to permitting under State Regulations 9 VAC 5-80-50, 9 VAC 5-80-1100, 9 VAC 5-80-1605, or 9 VAC 5-80-2000 and may require a permit modification and/or revisions except as may be authorized in any approved alternative operating scenarios.

(9 VAC 5-80-190 and 9 VAC 5-80-260)

K. Property Rights

The permit does not convey any property rights of any sort, or any exclusive privilege.

(9 VAC 5-80-110 G.5)

L. Duty to Submit Information

1. The permittee shall furnish to the Board, within a reasonable time, any information that the Board may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the Board copies of records required to be kept by the permit and, for information claimed to be confidential, the permittee shall furnish such records to the Board along with a claim of confidentiality.

(9 VAC 5-80-110 G.6)

2. Any document (including reports) required in a permit condition to be submitted to the Board shall contain a certification by a responsible official that meets the requirements of 9 VAC 5-80-80 G.

(9 VAC 5-80-110 K.1)

M. Duty to Pay Permit Fees

The owner of any source for which a permit under 9 VAC 5-80-50 through 9 VAC 5-80-300 was issued shall pay permit fees consistent with the requirements of 9 VAC 5-80-310 through 9 VAC 5-80-350. The actual emissions covered by the permit program fees for the preceding year shall be calculated by the owner and submitted to the Department by April 15 of each year. The calculations and final amount of emissions are subject to verification and final determination by the Department.

(9 VAC 5-80-110 H and 9 VAC 5-80-340 C)

N. Fugitive Dust Emission Standards

During the operation of a stationary source or any other building, structure, facility, or installation, no owner or other person shall cause or permit any materials or property to be handled, transported, stored, used, constructed, altered, repaired, or demolished without taking reasonable precautions to prevent particulate matter from becoming airborne. Such reasonable precautions may include, but are not limited to, the following:

1. Use, where possible, of water or chemicals for control of dust in the demolition of existing buildings or structures, construction operations, the grading of roads, or the clearing of land;

2. Application of asphalt, water, or suitable chemicals on dirt roads, materials stockpiles, and other surfaces which may create airborne dust; the paving of roadways and the maintaining of them in a clean condition;
3. Installation and use of hoods, fans, and fabric filters to enclose and vent the handling of dusty material. Adequate containment methods shall be employed during sandblasting or similar operations;
4. Open equipment for conveying or transporting material likely to create objectionable air pollution when airborne shall be covered or treated in an equally effective manner at all times when in motion; and,
5. The prompt removal of spilled or tracked dirt or other materials from paved streets and of dried sediments resulting from soil erosion.

(9 VAC 5-50-90)

O. Startup, Shutdown, and Malfunction

At all times, including periods of startup, shutdown, and soot blowing, and malfunction, owners shall, to the extent practicable, maintain and operate any affected facility including associated air pollution control equipment in a manner consistent with air pollution control practices for minimizing emissions. Determination of whether acceptable operating and maintenance procedures are being used will be based on information available to the Board, which may include, but is not limited to, monitoring results, opacity observations, review of operating and maintenance procedures, and inspection of the source.

(9 VAC 5-50-20 E)

P. Alternative Operating Scenarios

Contemporaneously with making a change between reasonably anticipated operating scenarios identified in this permit, the permittee shall record in a log at the permitted facility a record of the scenario under which it is operating. The permit shield described in 9 VAC 5-80-140 shall extend to all terms and conditions under each such operating scenario. The terms and conditions of each such alternative scenario shall meet all applicable requirements including the requirements of 9 VAC 5 Chapter 80, Article 1.

(9 VAC 5-80-110 J)

Q. Inspection and Entry Requirements

The permittee shall allow DEQ, upon presentation of credentials and other documents as may be required by law, to perform the following:

1. Enter upon the premises where the source is located or emissions-related activity is conducted, or where records must be kept under the terms and conditions of the permit.
2. Have access to and copy, at reasonable times, any records that must be kept under the terms and conditions of the permit.
3. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit.
4. Sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit or applicable requirements.

(9 VAC 5-80-110 K.2)

R. Reopening For Cause

The permit shall be reopened by the Board if additional federal requirements become applicable to a major source with a remaining permit term of three years or more. Such reopening shall be completed no later than 18 months after promulgation of the applicable requirement. No such reopening is required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions has been extended pursuant to 9 VAC 5-80-80 F.

1. The permit shall be reopened if the Board or the administrator determines that the permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of the permit.
2. The permit shall be reopened if the administrator or the Board determines that the permit must be revised or revoked to assure compliance with the applicable requirements.
3. The permit shall not be reopened by the Board if additional applicable state requirements become applicable to a major source prior to the expiration date established under 9 VAC 5-80-110 D.
(9 VAC 5-80-110 L)

S. Permit Availability

Within five days after receipt of the issued permit, the permittee shall maintain the permit on the premises for which the permit has been issued and shall make the permit immediately available to DEQ upon request.

(9 VAC 5-80-150 E)

T. Transfer of Permits

1. No person shall transfer a permit from one location to another, unless authorized under 9 VAC 5-80-130, or from one piece of equipment to another.
(9 VAC 5-80-160)
2. In the case of a transfer of ownership of a stationary source, the new owner shall comply with any current permit issued to the previous owner. The new owner shall notify the Board of the change in ownership within 30 days of the transfer and shall comply with the requirements of 9 VAC 5-80-200.
(9 VAC 5-80-160)
3. In the case of a name change of a stationary source, the owner shall comply with any current permit issued under the previous source name. The owner shall notify the Board of the change in source name within 30 days of the name change and shall comply with the requirements of 9 VAC 5-80-200.
(9 VAC 5-80-160)

U. Malfunction as an Affirmative Defense

1. A malfunction constitutes an affirmative defense to an action brought for noncompliance with technology-based emission limitations if the requirements of paragraph 2 of this condition are met.
2. The affirmative defense of malfunction shall be demonstrated by the permittee through properly signed, contemporaneous operating logs, or other relevant evidence that show the following:
 - a) A malfunction occurred and the permittee can identify the cause or causes of the malfunction.
 - b) The permitted facility was at the time being properly operated.
 - c) During the period of the malfunction the permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards, or other requirements in the permit.

- d) The permittee notified the Board of the malfunction within two working days following the time when the emission limitations were exceeded due to the malfunction. This notification shall include a description of the malfunction, any steps taken to mitigate emissions, and corrective actions taken. The notification may be delivered either orally or in writing. The notification may be delivered by electronic mail, facsimile transmission, telephone, or any other method that allows the permittee to comply with the deadline. This notification fulfills the requirements of 9 VAC 5-80-110 F.2.b to report promptly deviations from permit requirements. This notification does not release the permittee from the malfunction reporting requirement under 9 VAC 5-20-180 C.
3. In any enforcement proceeding, the permittee seeking to establish the occurrence of a malfunction shall have the burden of proof.
4. The provisions of this section are in addition to any malfunction, emergency or upset provision contained in any applicable requirement.
(9 VAC 5-80-250)

V. Permit Revocation or Termination for Cause

A permit may be revoked or terminated prior to its expiration date if the owner knowingly makes material misstatements in the permit application or any amendments thereto or if the permittee violates, fails, neglects or refuses to comply with the terms or conditions of the permit, any applicable requirements, or the applicable provisions of 9 VAC 5 Chapter 80 Article 1. The Board may suspend, under such conditions and for such period of time as the Board may prescribe any permit for any grounds for revocation or termination or for any other violations of these regulations.
(9 VAC 5-80-190 C and 9 VAC 5-80-260)

W. Duty to Supplement or Correct Application

Any applicant who fails to submit any relevant facts or who has submitted incorrect information in a permit application shall, upon becoming aware of such failure or incorrect submittal, promptly submit such supplementary facts or corrections. An applicant shall also provide additional information as necessary to address any requirements that become applicable to the source after the date a complete application was filed but prior to release of a draft permit.
(9 VAC 5-80-80 E)

X. Stratospheric Ozone Protection

If the permittee handles or emits one or more Class I or II substances subject to a standard promulgated under or established by Title VI (Stratospheric Ozone Protection) of the federal Clean Air Act, the permittee shall comply with all applicable sections of 40 CFR Part 82, Subparts A to F.
(40 CFR Part 82, Subparts A-F)

Y. Asbestos Requirements

The permittee shall comply with the requirements of National Emissions Standards for Hazardous Air Pollutants (40 CFR 61) Subpart M, National Emission Standards for Asbestos as it applies to the following: Standards for Demolition and Renovation (40 CFR 61.145), Standards for Insulating Materials (40 CFR 61.148), and Standards for Waste Disposal (40 CFR 61.150).
(9 VAC 5-60-70 and 9 VAC 5-80-110 A.1)

Z. Accidental Release Prevention

If the permittee has more, or will have more than a threshold quantity of a regulated substance in a process, as determined by 40 CFR 68.115, the permittee shall comply with the requirements of 40 CFR Part 68.

(40 CFR Part 68)

AA. Changes to Permits for Emissions Trading

No permit revision shall be required under any federally approved economic incentives, marketable permits, emissions trading and other similar programs or processes for changes that are provided for in this permit.

(9 VAC 5-80-110 I)

BB. Emissions Trading

Where the trading of emissions increases and decreases within the permitted facility is to occur within the context of this permit and to the extent that the regulations provide for trading such increases and decreases without a case-by-case approval of each emissions trade:

1. All terms and conditions required under 9 VAC 5-80-110, except subsection N, shall be included to determine compliance.
2. The permit shield described in 9 VAC 5-80-140 shall extend to all terms and conditions that allow such increases and decreases in emissions.
3. The owner shall meet all applicable requirements including the requirements of 9 VAC 5-80-50 through 9 VAC 5-80-300.

(9 VAC 5-80-110 I)

XI. State-Only Enforceable Requirements

The following terms and conditions are not required under the federal Clean Air Act or under any of its applicable federal requirements, and are not subject to the requirements of 9 VAC 5-80-290 concerning review of proposed permits by EPA and draft permits by affected states.

9 VAC 5, Chapter 40, Part II, Article 2: Emissions Standards for Odor

9 VAC 5, Chapter 50, Part II, Article 2: Standards of Performance for Odorous Emissions

9 VAC 5, Chapter 60, Part II, Article 4: Emission Standards for Toxic Pollutants from Existing Sources

9 VAC 5, Chapter 60, Part II, Article 5: Emission Standards for Toxic Pollutants from New and Modified Sources

(9 VAC 5-80-110 N and 9 VAC 5-80-300)